



- Economical design, available with PC terminals or wire leads
- Batteries securely held in place to assure a positive connection and maintain a low contact resistance
- Contact springs self-adjust to variations in battery length
- Withstands shock and vibration
- Available with solder lugs or male/female snap fasteners
- For easy removal, available with ribbon

### SPECIFICATIONS


**Holder:** Polypropylene  
**Springs:** Spring Steel, Nickel Plate  
**PC Pins:** .031 (.79) thick Brass, Nickel Plate  
**Wires (Red & Black):** #26 AWG, Tinned, .187 (4.8) end strip UL/CSA1007

### MODIFICATIONS

We welcome the opportunity to quote on variations of standard items. Use our Engineering services for your custom-built holders. Holders for "C" and "D" cell are available on request.


## For "AA" - "AAA"

### Holds One (1) "AA" Cell




<b>CAT. NO. 2460</b>	PC Mount
<b>CAT. NO. 2460RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2461</b>	Wire Leads - 6.0 (150)

### Holds Two (2) "AA" Cells in Series




<b>CAT. NO. 2462</b>	PC Mount
<b>CAT. NO. 2462RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2463</b>	Wire Leads - 6.0 (150)

### Holds Three (3) "AA" Cells in Series




<b>CAT. NO. 2464</b>	PC Mount
<b>CAT. NO. 2464RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2465</b>	Wire Leads - 6.0 (150)

### Holds Four (4) "AA" Cells in Series




<b>CAT. NO. 2477</b>	PC Mount
<b>CAT. NO. 2477RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2478</b>	Wire Leads - 6.0 (150)

### Holds One (1) "AAA" Cell




<b>CAT. NO. 2466</b>	PC Mount
<b>CAT. NO. 2466RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2467</b>	Wire Leads - 6.0 (150)

### Holds Two (2) "AAA" Cells in Series




<b>CAT. NO. 2468</b>	PC Mount
<b>CAT. NO. 2468RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2469</b>	Wire Leads - 6.0 (150)

### Holds Three (3) "AAA" Cells in Series



<b>CAT. NO. 2479</b>	PC Mount
<b>CAT. NO. 2479RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2480</b>	Wire Leads - 6.0 (150)


### Holds Four (4) "AAA" Cells in Series



<b>CAT. NO. 2481</b>	PC Mount
<b>CAT. NO. 2481RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2482</b>	Wire Leads - 6.0 (150)


## For "1/2 AA" - "N"

### Holds One (1) "1/2 AA" Cell




<b>CAT. NO. 2485</b>	PC Mount
<b>CAT. NO. 2485RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2486</b>	Wire Leads - 6.0 (150)

### Holds One (1) "N" Cell



<b>CAT. NO. 2470</b>	PC Mount
<b>CAT. NO. 2470RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2471</b>	Wire Leads - 6.0 (150)

### Holds Two (2) "N" Cells in Series



<b>CAT. NO. 2472</b>	PC Mount
<b>CAT. NO. 2472RB</b>	PC Mount w/ribbon
<b>CAT. NO. 2473</b>	Wire Leads - 6.0 (150)