

SPECIFICATION

CUSTOMER:		DATE:													
PART NO: DS3316-680M		DWG.NO:													
CUSTOMER PART NO:		CUST.DWG.NO:													
<p>(1) DIMENSION(UNIT: mm)</p>		A	9.50 (MAX)	m/m											
		B	13.50 (MAX)	m/m											
		C	5.21 (MAX)	m/m											
		D	2.54 (REF)	m/m											
		E	8.00 (REF)	m/m											
		F		m/m											
		G		m/m											
		H		m/m											
		I		m/m											
		J		m/m											
		<p>(2)ELECTRICAL REQUIREMENTS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">L (uH)</td> <td style="text-align: center;">68 ± 20%</td> </tr> <tr> <td>RDC (Ω)</td> <td style="text-align: center;">0.2 (MAX)</td> </tr> <tr> <td>IDC (A)</td> <td style="text-align: center;">2 (MAX)</td> </tr> <tr> <td>TEST CONDITION</td> <td style="text-align: center;">100KHZ / 0.1V</td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </table>		L (uH)	68 ± 20%	RDC (Ω)	0.2 (MAX)	IDC (A)	2 (MAX)	TEST CONDITION	100KHZ / 0.1V				
L (uH)	68 ± 20%														
RDC (Ω)	0.2 (MAX)														
IDC (A)	2 (MAX)														
TEST CONDITION	100KHZ / 0.1V														
<p>APPROVED BY</p> <p>CHECKED BY</p> <p>DRAWN BY</p>															

TEST DATA

CUSTOMER:				DATE:			
PART NO: DS3316-680M				DWG.NO:			
CUSTOMER PART NO :				CUST.DWG.NO :			
TEST CONDITION: 100KHZ / 0.1V				DIMENSION (UNIT : mm)			
ITEM	L (uH)	RDC (Ω)	IDC (A)	A	B	C	
SPEC	68 ± 20%	0.2 (MAX)	2 (MAX)	9.50 (MAX)	13.50 (MAX)	5.21 (MAX)	
1	68.6	0.178	OK	9.24	12.97	4.93	
2	68.3	0.181	OK	9.24	12.93	4.92	
3	68.4	0.178	OK	9.23	13.03	4.97	
4	69.1	0.178	OK	9.19	12.84	5.03	
5	67.8	0.178	OK	9.21	12.94	4.87	
6	68.3	0.178	OK	9.29	12.94	4.93	
7	68.7	0.177	OK	9.22	12.87	4.93	
8	68.0	0.183	OK	9.24	13.05	4.97	
9	68.9	0.184	OK	9.24	13.00	4.96	
10	67.3	0.184	OK	9.23	12.97	4.99	
\bar{X}	68.34	0.18		9.233	12.954	4.95	
R	1.8	0.007		0.1	0.21	0.16	
TEST INSTRUMENTS DV-6021 LCR METER VR-131 RDC METER CH-301A BA/S CURRENT				APPROVED BY			
				CHECKED BY			
				DRAWN BY			