




XBee® Family Features Comparison

| Protocol | Product | Frequency | Description | RF Line of Sight Range | Form Factor | MSRP | RF Data Rate | Current Draw Tx/Rx | Hardware | Certified Regions |
|---|---------------------|--------------------|--|------------------------|-------------------|---------|---------------------|--------------------|----------|------------------------|
| IEEE 802.11 | XBee® Wi-Fi | 2.4 GHz | Wi-Fi 802.11b/g/n with easy provisioning, native Device Cloud features | N/A | Through-hole, SMT | \$35.00 | 1 to 72 Mbps | 309 mA / 100 mA | S6B | US, CA, EU, AU, JP |
| IEEE 802.15.4  | XBee® 802.15.4 | 2.4 GHz | Best way to get started with point-to-multipoint device connectivity | 300 ft / 90 m | Through-hole | \$19.00 | 250 Kbps | 45 mA / 50 mA | S1 | US, CA, EU, AU, BR, JP |
| | XBee-PRO® 802.15.4 | 2.4 GHz | Point-to-multipoint extended range version | 1 mile / 1.6 km | | \$32.00 | 250 Kbps | 215 mA / 55 mA | S1 | US, CA, AU, BR |
| | | 2.4 GHz | International/"J" variant | 2500 ft / 1 km | | \$32.00 | 250 Kbps | | S1 | US, CA, EU, AU, BR, JP |
| <hr/> | | | | | | | | | | |
| Multipoint Proprietary  | XBee-PRO® XSC | 900 MHz | Long-range proprietary multipoint connectivity | 9 miles / 14.5 km | Through-hole | \$39.00 | 10 Kbps or 20 Kbps | 215 mA / 26 mA | S3B | US, CA, AU |
| | XBee-PRO® 868 | 868 MHz | Long-range multipoint for Europe | 25 miles / 40 km | | \$45.00 | 24 Kbps | 500 mA / 65 mA | S5 | EU |
| <hr/> | | | | | | | | | | |
| ZigBee® PRO Feature Set  | XBee® ZB SMT | 2.4 GHz | ZigBee mesh networking, low-cost, low-power, surface mount | 4000 ft / 1.2 km | SMT | \$17.50 | 250 Kbps | 45 mA / 28 mA | S2C | US, CA, EU, AU, BR, JP |
| | XBee-PRO® ZB SMT | 2.4 GHz | Extended-range ZigBee, surface mount | 2 miles / 3.2 km | | \$28.50 | 250 Kbps | 100 mA / 31 mA | S2C | US, CA, AU, BR |
| | XBee® ZB | 2.4 GHz | ZigBee mesh, low-cost, low-power, through-hole | 400 ft / 120 m | Through-hole | \$17.00 | 250 Kbps | N/A | S2 | US, CA, EU, AU, BR, JP |
| | XBee-PRO® ZB | 2.4 GHz | Extended-range ZigBee, through-hole | 2 miles / 3.2 km | | \$28.00 | 250 Kbps | 205 mA / 47 mA | S2B | US, CA, AU, BR |
| | | 2.4 GHz | International/"J" variant | 5000 ft / 1.5 km | | \$28.00 | 250 Kbps | | S2B | US, CA, EU, AU, BR, JP |
| <hr/> | | | | | | | | | | |
| DigiMesh® Proprietary  | XBee-PRO® 900HP | 900 MHz | Extended-range peer-to-peer mesh, sleeping routers (900 MHz) | 9 miles / 14.5 km | Through-hole | \$39.00 | 10 Kbps or 200 Kbps | 215 mA / 29 mA | S3B | US, CA, AU, BR |
| | XBee® 865/868LP | 865 MHz or 868 MHz | Low-power peer-to-peer mesh for India (865 MHz) or Europe (868 MHz) | 2.5 miles / 4 km | SMT | \$23.00 | 10 Kbps or 80 Kbps | 48 mA / 27 mA | S8 | India, EU |
| | XBee® DigiMesh® 2.4 | 2.4 GHz | Low-cost, low-power peer-to-peer mesh, sleeping routers | 300 ft / 90 m | Through-hole | \$19.00 | 250 Kbps | 45 mA / 50 mA | S1 | US, CA, EU, AU, BR, JP |
| | | 2.4 GHz | Extended-range peer-to-peer mesh, sleeping routers (2.4 GHz) | 1 mile / 1.6 km | | \$32.00 | 250 Kbps | 250 mA / 55 mA | S1 | US, CA, AU, BR |
| | | 2.4 GHz | International/"J" variant | 3200 ft / 1 km | | \$32.00 | 250 Kbps | 150 mA / 55 mA | S1 | US, CA, EU, AU, BR, JP |

