

Industry FSP180-1H35-12

DESCRIPTION

180W Open frame type power supply with 12V DC output for information technolegy and industrial applications

APPLICATION

For information technolegy and industrial applications

FEATURES

WATTAGE Wattage:

Size:

- Compact size 3' x 5" x 1.32"
 100~180W with 10CFM forced airflow
- 100W with free air convection
 EN55022 class B emissions
- MTBF 100,000 hours

PRODUCT HIGHLIGHT Efficiency Level: Output Voltage:

INPUT SPECIFICATION

OUTPUT SPECIFICATION Output Voltage/Current:

Input Type: Input Voltage:

Input Frequency: Input Current:

Inrush current: Earth leakage current

Output1

12 V , 15 A **Ripple & Noise:** Output1 200mV



SAFETY STANDARD APPAOVAL

c**51.**®us

	ENVIRONMENTAL SPECIFICATION	
180W	Storage temperature: Relative humidity:	-20 $^{\circ}$ C to +80 $^{\circ}$ C 5% to 90% non-condensing
	GENERAL SPECIFICATION	
85% / 115Vac & 88% / 230Vac 12 VDC 76.2 (3") x 127 (5") x 33.6 (1.32") mm	Efficiency: Hold-up time:	85% /115Vac & 88% / 230Vac @Full Road% minimum on all models 16 / 18 ms minimum at 16 / 18 VAC
1	MTBF:	100,000 hours minimum at
AC-DC 90~132 Vac 47~63 Hz 3.0A : 110 VAC / 230 Full Road		full load at 25 °C ambient, calculated per MIL-HDBK- 217F
50A @115VAC ; 100A @ 230VAC	EMC PERFORMANCE	
3.5 mA max. @ 115VAC, 60Hz / 230VAC, 50Hz	EN55022:	Class B Conducted, Class B radiated
DN	FCC:	Class B Conducted, Class B radiated
ent:	EN61000-4-2:	ESD, ±15 KV Air ; ± 8 KV contact
	EN61000-4-4: EN61000-4-5:	Fast transient/burst, ±2 KV Surge, ±1 KV diff., ±2 KV com.

MECHANICAL **Dimension:** 76.2mm(L) x 127mm(W) x 33.6mm(H) 100W / convection; 100W ~ 180W with 10CFM forced **Cooling:** airflow **Connector Type-Input:** JWT A3963WV2-5P or equivalent JWT A3963WV2-8P or **Conntector Type-Output:** equivalent **Remote Control:** No

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice