

Part Number: KTIR0821DS


*Features

- Compact and thin
- Visible light cut-off type
- High sensitivity
- RoHS Compliant.

*Applications

- Cassette tape recorders, VCRs
- Floppy disk drives
- Various microcosm puterized control equipment

Package Dimensions



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25(0.01") unless otherwise noted.
3. Lead spacing is measured where the leads emerge from the package.
4. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.

*Absolute Maximum Ratings (Ta=25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I _F	50	mA
	Reverse voltage	V _R	6	V
	Power dissipation	P _d	75	mW
	Peak Forward Current (Pulse Width ≤100uS, Duty Cycle =1%)	I _{FP}	1	A
Output	Collector-emitter voltage	V _{C EO}	35	V
	Emitter-collector voltage	V _{E CO}	6	V
	Collector current	I _C	50	mA
	Collector power dissipation	P _C	75	mW
Operating temperature		T _{opr}	-25~+85	°C
Storage temperature		T _{stg}	-40~+100	°C
Soldering temperature (1/16 inch from body for 5 seconds)		T _{sol}	260	°C



■ Electro-optical Characteristics ($T_a=25^\circ C$)

Parameter		Symbol	Conditions	Min.	TYP.	Max.	Unit
Input	Forward Voltage	V_F	$I_F=20mA$	1.0	1.2	1.5	V
	Reverse Current	I_R	$V_R=6V$	-	-	10	μA
	Peak Wavelength	λP	$I_F=20mA$	-	940	-	nm
Output	Collector Dark Current	I_{CEO}	$V_{CE}=10V$ $I_F=0mA$	-		10^{-6}	A
Transfer characteristics	* ¹ Collector Current	I_C	$V_{CE}=2V$ $I_F=4mA$	-	3	-	mA
	* ² Leak Current	I_{LEAK}	$V_{CE}=5V$ $I_F=4mA$	-	-	5	μA
	Response time	tr	$V_{CE}=2V$ $I_C=10mA$	-	80	400	μsec
	Fall time	tf	$R_L=100\Omega, d=1mm$	-	70	400	μsec

*1 The condition and arrangement of the reflective object are shown below

*2 Without reflective object




Fig. 1 Forward Current vs.
Forward Voltage




Fig. 3 Collector Current vs.
Collector-emitter Voltage

Fig. 2 Collector Current vs.
Forward Current




Fig. 4 Relative Collector Current vs.
Ambient Temperature






Fig. 5 Response Time vs.
Load Resistance



Test Circuit for Response Time




Fig. 6 Collector Dark Current vs. Fig. 7 Relative Collector Current vs.
Ambient Temperature




Fig. 7 Relative Collector Current vs.
Distance between Sensor and
Al Evaporation Glass




Fig. 8 Relative Collector Current vs. Fig. 9 Relative Collector Current vs.
Card Moving Distance (1)






Fig. 9 Relative Collector Current vs.
Card Moving Distance (2)



Test Condition for Distance & Detecting Position Characteristics

Correspond to Fig. 7



Correspond to Fig. 8

Test condition

$$I_F = 4 \text{ mA}$$

$$V_{CE} = 2 \text{ V}$$

$$d = 1 \text{ mm}$$




Correspond to Fig. 9

Test condition

$$I_F = 4 \text{ mA}$$

$$V_{CE} = 2 \text{ V}$$

$$d = 1 \text{ mm}$$




PACKING & LABEL SPECIFICATIONS


KTIR0821DS




150PCS / IC TUBE




1500PCS / 10PCS IC TUBE



OUTSIDE LABEL



10PCS IC TUBE / BAG



Detailed application notes are listed on our website.

http://www.kingbright.com/application_notes