


M 2401



Euromas
Enclosure, polycarbonate
Order no.: 02240200

| | |
|----------------------------------|--|
| Colour of enclosure group | Light grey, similar to RAL 7035; special colours on request |
| Protection class | Depending on the model: IP 65 or IP 66/DIN EN 60529; IP 67 available on request for some sizes. |
| Enclosure material | ABS, PC (UV stabilised) and selected sizes in PC UL 94 V0 (additional UL 94 V0 versions on request), seal made of CR; for details see Technical Information |
| Scope of delivery | Scope of delivery: Lid and base, lid screws made of V2A, self-tapping screws for mounting bosses Note: G = Design with crystal-clear lid. IP = Ingress protection acc. to DIN EN 60529 |



| | |
|-----------|----------|
| A | 240,3 mm |
| B | 160,3 mm |
| C | 90 mm |
| a1 | 233 mm |
| a2 | 214,7 mm |
| b1 | 153 mm |
| b2 | 116,7 mm |
| b3 | 134,7 mm |
| c1 | 15 mm |
| c2 | 84 mm |

| | |
|---------------------------|--|
| Technical drawings | 3D product data in STEP format: Registration necessary Basic drawing for processing work: 02240200_M-401-G.dxf (393 KB) Catalogue drawing in DXF format: 02240200_M-2401.dxf (727 KB) Catalogue drawing in PDF format: 02240200_M-2401.pdf (107 KB) |
| Chapter download | Euromas_ABS_PC_GB.pdf (338 KB) |

* = Available on request