



Technical Specifications

Battery Charger:	Class 2, Power Supply
Plug:	Direct Plug-In Matches Local Requirements
Battery Type/Fit:	NiMH: 2 or 4 AA/HR6, NiMH: 2 or 4 AAA/HR03
Typical Weight:	207 g
Input:	100-240V AC, 50/60 Hz, 7w
Output:	AA/HR6: 3.0V DC 360 mA AAA/HR03: 3.0V DC 180 mA
Operating Temp:	0°C - 35°C (32°F - 95°F)
Dimensions:	123 mm (H) x 72 mm (W) x 42 mm (D)

BENEFITS

Great Value, New Sleek & Compact Design, Convenient Wall Plug-In

FEATURES

Independent Channel Charging

- Fully charges cell in 6 hours*
- Charges both AA and AAA NiMH cells
- Ensures a full charge regardless of charge or battery capacity

LED Indicates Charge

- Red = Charging
- Green = Complete
- Blinking Red = Error/Abnormal battery or abnormal temperature
- Blinking Green = Ready to Use

Maintenance Charge Keeps Cells Fresh

International Charge Capability – device can be used worldwide with suitable converter plug

SAFETY

Microprocessor Controlled

- Charge Termination based on – dV/dt, temperature, and/or built in timer
- Over-temperature shut off – prevents overheat of cell
- Primary cell protection – will not charge non-rechargeable batteries
- Low-voltage battery protection – prevents overheat and damage to cell
- Power protection circuit – resets whenever a battery is removed

DURACELL®
BATTERIES

Berkshire Corporate Park
Bethel, CT 06801 U.S.A.
Tel: Toll free 1.800.544.5454
Web: www.Duracell.com

*Charge rate and time is dependent on cell capacity, discharge state, and operating temperature

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without prior notice. For most current information and further details, please contact Duracell.