

---


## ATWINC3400 Wi-Fi® Network Controller Xplained Pro User Guide

---

### Introduction

---

The ATWINC3400-XPRO is an extension board to evaluate the performance of the ATWINC3400-MR210CA, an IEEE® 802.11 b/g/n RF/Baseband/MAC Network Controller with Integrated Low Energy Bluetooth® 4.0 compliant module. The ATWINC3400 Xplained Pro extension is designed to provide Wi-Fi® and Bluetooth functionality in 2.4 GHz ISM band to the Xplained Pro evaluation platform. This kit provides easy access to the features of the ATWINC3400-MR210CA and explains how to integrate the device in a custom design.



### Features

---

- The **ATWINC3400-MR210CA**: IEEE 802.11 b/g/n Link Controller with Integrated Low Energy Bluetooth 4.0 compliant module features the following:
  - IEEE 802.11 b/g/n 20MHz (1x1) Wi-Fi solution
    - Single spatial stream, up to 72 Mbps PHY rate in 2.4 GHz ISM band
    - Network features: Firmware version 1.2.x, TCP, UDP, DHCP, ARP, HTTP, SSL, DNS, and SNTP
    - Host interface through SPI
  - Bluetooth Low Energy (BLE) 4.0
    - Adaptive Frequency Hopping
    - Host Control Interface (HCI) through high speed UART

- Integrated PA, T/R switch and chip antenna
- Superior sensitivity and range
- On-Chip Network Stack to offload MCU
- Integrated flash memory for system software
- I<sup>2</sup>C and UART host interfaces
- Operating temperature range of -40 to +85°C
- Debug I<sup>2</sup>C and UART headers
- Current Measurement header
- Optional SPI flash boot
- ATECC508A Crypto Authentication Device
  - Ideal for IoT node security
  - Secure hardware-based Key Storage
  - Internal High-quality FIPS Random Number Generator
- Xplained Pro extension hardware identification system

## Table of Contents


---

Introduction.....	1
Features.....	1
1. Kit Overview.....	4
2. Getting Started.....	5
2.1. Xplained Pro Quick Start.....	5
2.2. Design Documentation and Relevant Links.....	5
3. Xplained Pro.....	6
3.1. Hardware Identification System.....	6
3.2. Xplained Pro Standard Extension Header.....	6
4. Hardware Users Guide.....	8
4.1. Headers and Connectors.....	8
4.2. ATWINC3400-XPRO Peripherals.....	10
5. Hardware Revision History and Known Issues.....	12
5.1. Identifying Product ID and Revision.....	12
5.2. Revision.....	12
6. Document Revision History.....	13
The Microchip Web Site.....	14
Customer Change Notification Service.....	14
Customer Support.....	14
Microchip Devices Code Protection Feature.....	14
Legal Notice.....	15
Trademarks.....	15
Quality Management System Certified by DNV.....	16
Worldwide Sales and Service.....	17

### 1. Kit Overview

The ATWINC3400-XPRO is a carrier board for the SmartConnect-ATWINC3400-MR210CA Wi-Fi/BLE module for the Xplained Pro platform. It connects to any Xplained Pro standard extension header on any Xplained Pro MCU board to provide Wi-Fi/BLE functionality.

Figure 1-1. ATWINC3400-XPRO



## 2. Getting Started

The ATWINC3400-XPRO has been designed to be connected to an Xplained Pro extension header marked as EXT1. However, it is compatible with all Xplained Pro extension headers. Refer to the pin-out of your Xplained Pro evaluation kit to find out which Xplained Pro extension headers can be used.

### 2.1 Xplained Pro Quick Start

Steps to start exploring the Xplained Pro platform:

1. Download and install [Atmel Studio](#).
2. Launch Atmel Studio.

When the Xplained Pro MCU kit is connected to the computer for the first time, the operating system installs the driver software automatically. This driver supports 32-bit and 64-bit versions of Microsoft® Windows® XP, Windows Vista®, Windows 7, Windows 8, Windows 10, and Windows Server 2012.

When the Xplained Pro MCU board is powered, the power LED (green) glows and the Atmel Studio automatically detects the specific Xplained Pro MCU and extension board(s) that are connected. The landing page of the kit in the Atmel Studio has an option to launch the Atmel Software Framework (ASF) and the Atmel START example application codes for the kit. The target device is programmed and debugged by the on-board embedded debugger and therefore no external programmer or debugger tool is required.

### 2.2 Design Documentation and Relevant Links

The following list contains the links to the most relevant documents and software for ATWINC3400-XPRO:

- [Xplained Pro products](#) - Atmel Xplained Pro is a series of small-sized and easy-to-use evaluation kits for Atmel microcontrollers and other Atmel products. It consists of a series of low-cost MCU boards for evaluation and demonstration of features and capabilities of different MCU families.
- [ATWINC3400-XPRO User Guide](#)- Product documents page.
- [ATWINC3400-XPRO Design Documentation](#)- Package containing schematics, BOM, assembly drawings, 3D plots, layer plots, etc.
- [Atmel Studio](#)- Free Atmel IDE for development of C/C++ and assembler code for Atmel microcontrollers.
- [EDBG User Guide](#)- User guide containing more information about the on board Embedded Debugger.
- [Atmel Data Visualizer](#) - Atmel Data Visualizer is a program used for processing and visualizing data. Data Visualizer can receive data from various sources such as the Embedded Debugger Data Gateway Interface found on Xplained Pro boards and COM ports.
- [ATWINC3400-XPRO](#)- Product page.
- [ATWINC3400-MR210CA](#)- Wireless module datasheet.
- [ATWINC3400](#)- Wireless chip datasheet.
- [ATWINC3400 BLE Provisioning – Setup and Usage](#)- Application Note.
- [ATECC508A-MAHDA-T](#)- Crypto Authentication Device datasheet.
- [AT24MAC602-STUM-T](#)- Serial EEPROM datasheet.

### 3. Xplained Pro

Xplained Pro is an evaluation platform which contains a series of microcontroller boards (evaluation kits) and extension boards. Atmel Studio is used to program and debug the microcontrollers on these boards. Atmel Studio includes ASF and Atmel START, which has drivers and demo code, and Data Visualizer, which supports data streaming and advanced debugging. Xplained Pro evaluation kits can be connected to a wide range of Xplained Pro extension boards through standardized headers and connectors. Xplained Pro extension boards have identification (ID) chips to uniquely identify which boards are connected to the Xplained Pro evaluation kits.

#### 3.1 Hardware Identification System

All Xplained Pro extension boards come with an identification chip (ATSHA204A CryptoAuthentication™ chip) to uniquely identify the boards that are connected to the Xplained Pro evaluation kit. This chip contains information that identifies the extension with its name and some extra data. When an Xplained Pro extension is connected to an Xplained Pro evaluation kit, the information is read and sent to the Atmel Studio. The following table shows the data fields stored in the ID chip with example content.

**Table 3-1. Xplained Pro ID Chip Content**

Data Field	Data Type	Example Content
Manufacturer	ASCII string	Microchip\0'
Product name	ASCII string	Segment LCD1 Xplained Pro\0'
Product revision	ASCII string	02\0'
Product serial number	ASCII string	1774020200000010\0'
Minimum voltage [mV]	uint16_t	3000
Maximum voltage [mV]	uint16_t	3600
Maximum current [mA]	uint16_t	30

#### 3.2 Xplained Pro Standard Extension Header

All Xplained Pro kits have many dual row, 20-pin, 100-mil extension headers. The Xplained Pro MCU boards have male headers, while the Xplained Pro extensions have their female counterparts. The following table provides the pin description of all the connected pins.



**Info:** Not all pins are always connected on all extension headers.

The extension headers can be used to connect a variety of Xplained Pro extensions to Xplained Pro MCU boards or to access the pins of the target microcontroller on the Xplained Pro boards.

**Table 3-2. Xplained Pro Standard Extension Header**

Pin Number	Pin Name	Description
1	ID	Pin to communicate with the ID chip on an extension board.
2	GND	Ground
3	ADC(+)	Analog-to-Digital Converter; alternatively, a pin for the positive terminal of a differential ADC.
4	ADC(-)	Analog-to-Digital Converter; alternatively, a pin for the negative terminal of a differential ADC.
5	GPIO1	General purpose I/O pin.
6	GPIO2	General purpose I/O pin.
7	PWM(+)	Pulse width modulation; alternatively, a pin for the positive part of a differential PWM.
8	PWM(-)	Pulse width modulation; alternatively, a pin for the negative part of a differential PWM.
9	IRQ/GPIO	Interrupt request pin and/or general purpose I/O pin.
10	SPI_SS_B/ GPIO	Slave select pin for Serial Peripheral Interface (SPI) and/or general purpose I/O pin.
11	I <sup>2</sup> C_SDA	Data pin for I <sup>2</sup> C interface. Always connected, bus type.
12	I <sup>2</sup> C_SCL	Clock pin for I <sup>2</sup> C interface. Always connected, bus type.
13	UART_RX	Receiver pin of target device UART.
14	UART_TX	Transmitter pin of target device UART.
15	SPI_SS_A	Slave select for SPI. This pin should preferably not be connected to anything else.
16	SPI_MOSI	SPI master out slave in pin. Always connected, bus type.
17	SPI_MISO	SPI master in slave out pin. Always connected, bus type.
18	SPI_SCK	SPI clock pin. Always connected, bus type.
19	GND	Ground pin for extension boards.
20	VCC	Power pin for extension boards.

## 4. Hardware Users Guide

### 4.1 Headers and Connectors

#### 4.1.1 ATWINC3400-XPRO Extension Header

The ATWINC3400-XPRO implements one Xplained Pro Standard Extension Header marked with EXT in PCB silkscreen. This header makes it possible to connect the board to any Xplained Pro MCU board. The pin-out definition for the extension header can be seen below.

**Table 4-1. ATWINC3400-XPRO Extension Connector**

Pin on EXT	Function	Description
1	ID_DATA	Communication line to ID chip
2	GND	Ground
3	HOST_WAKEUP	Wakeup signal to the host from wireless module
4	RESET_N	Reset signal from Xpro's host MCU
5	UART_RTS	Request To Send (RTS) for 4-pin UART interface flow control/handshaking
6	UART_CTS	Clear To Send (CTS) for 4-pin UART interface flow control/handshaking
7	CHIP_EN	Secondary optional Chip enable signal for wireless module from host MCU of an XPRO in which pin 10 of EXT header can't be used for chip enable.
8	RTC_MCU	Real-time clock from Host MCU. It is secondary clock source. Primary clock is from on-board RTC oscillator.
9	IRQN	Interrupt request to host
10	CHIP_EN	Primary chip enable signal for wireless module from host MCU
11	I2C_SDA_S	Data line for slave I <sup>2</sup> C interface to ECC508
12	I2C_SCL_S	Clock line for slave I <sup>2</sup> C interface to ECC508
13	BT_UART1_TXD	Transmit pin of wireless module's UART interface
14	BT_UART1_RXD	Receive pin of wireless module's UART interface
15	SPI_SSN_WiFi	Slave select/Chip select signal of slave SPI interface for Wi-Fi
16	SPI_MOSI_WiFi	Master out-Slave in signal of slave SPI interface for Wi-Fi
17	SPI_MISO_WiFi	Master in-Slave out signal of slave SPI interface for Wi-Fi
18	SPI_SCK_WiFi	Clock line of slave SPI interface for Wi-Fi



Pin on EXT	Function	Description
19	GND	Ground
20	VCC_TARGET	Target +3.3V supply voltage from host MCU board

### 4.1.2 Power Measurement Header

Current measurement header (J102) can be used to measure the total current consumed by the ATWINC3400-MR210CA module using a voltmeter. To measure the total current consumption of the module, remove the jumper from J102 and connect a voltmeter across its pins. A 1Ω resistor available on board across the jumper gives a 1:1 relationship between voltage drop and current consumption.

There are two 0Ω resistors, R135 and R136, that can be removed one by one to connect the ammeter across the corresponding resistor pads to measure the current consumed by individual power rails of the ATWINC3400-MR210CA, VBAT and VDDIO respectively.

### 4.1.3 Debug Connectors

Debug I<sup>2</sup>C Header (J104) is mounted on the board. The connector and module pinouts are given below. This I<sup>2</sup>C connector is only for development debug. An I<sup>2</sup>C/SPI Host Adapter like **Aardvark** is required to connect J104 with PC GUI to program and debug.

**Table 4-2. Debug I<sup>2</sup>C Connector J104**

Pin on I <sup>2</sup> C connector	Pin on ATWINC3400-MR210CA module	Function
1	11	I <sup>2</sup> C SCL
2	1	Ground
3	10	I <sup>2</sup> C SDA
4	-	Not Connected

Debug UART Header (J103) is mounted on the board. This connector is for debug using this UART. A USB high speed to UART Cable like **FTDI** is required to connect J103 with PC to print debug log. The connector and module pinouts are given below.

**Note:** Remove R143 and R144 resistors for enabling the debug I2C Interface.

**Table 4-3. Debug UART Connector J103**

Pin on UART Connector	Pin on ATWINC3400-MR210CA module	Function
1	17	WiFi_UART_RXD
2	16	WiFi_UART_TXD
3	1	Ground

I<sup>2</sup>C and UART pins of wireless module are connected with Extension port receptacle J101. The connector can be used for connecting extension board or Debug purpose.

**Table 4-4. Extension Port / Debug Connector J101**

Pin on Extension Port	Pin on ATWINC3400-MR210CA module	Function
1	10	I2C_SDA_S
2	-	NC
3	11	I2C_SCL_S
4	9	BT_UART_RXD
5	1	GND
6	8	BT_UART_TXD
7	-	NC
8	1	GND
9	7	RESET_N
10	12 and 18	VCC_MODULE (+3.3V)

## 4.2 ATWINC3400-XPRO Peripherals

### 4.2.1 Serial Flash

The ATWINC3400-XPRO features an external SPI Flash. Master SPI interface of the ATWINC3400 is used for communication with Flash. Provision to assemble Flash on PCB is given; however, the device is not mounted on the board (Part number- AT25DF081A-SSH-T, Reference number - U104).

**Table 4-5. Serial Flash Connections**

Pin on ATWINC3400-MR210CA module	Function
14	SPI SCK
16	SPI MOSI
17	SPI MISO
15	SPI SS

### 4.2.2 LED

There is a dual green/red LED on the ATWINC3400-XPRO extension board that is controlled by the ATWINC3400-MR210CA. These LEDs are used to show the application status.

**Table 4-6. LED Connection**

Pin on ATWINC3400-MR210CA module	Function
29	Green LED
30	Red LED

### 4.2.3 Crypto Device

The ATWINC3400-XPRO features an ATECC508A CryptoAuthentication device. The device is mounted on the board (Part number- ATECC508A-MAHDA-T, Reference number - U101). The primary connection of

the device with the host MCU is through an I2C interface available at 20 pin header . Master I<sup>2</sup>C interface of the ATWINC3400 has been provided as optional secondary I2C communication interface with the crypto device.

**Table 4-7. ATECC508A Connections**

Pin on ATWINC3400-MR210CA module	Function
35	I <sup>2</sup> C data
34	I <sup>2</sup> C clock

### 4.2.4 EEPROM

The ATWINC3400-XPRO features an external EEPROM. Master I<sup>2</sup>C interface of the ATWINC3400 is used for communication with EEPROM. Provision to assemble EEPROM is given; however, the device is not mounted in board (Part number- AT24MAC602-STUM-T, Reference number - U102) .

**Table 4-8. EEPROM Connections**

Pin on ATWINC3400-MR210CA module	Function
35	I <sup>2</sup> C data
34	I <sup>2</sup> C clock

### 4.2.5 Test Points

Some test points are available for use on the board. TP101 and TP103 can be used in addition with SPI interface lines for SDIO interface which needs some hardware rework. TP103, TP104, TP105, and TP106 can be used for PCM interface by appropriately disconnecting the multiplexed alternate functionality. TP107, TP108, TP109, and TP110 pins are GPIO38, 39, 40, and 42 pins of the ATWINC3400 chip respectively.

**Table 4-9. Test Point Connections**

Test Point	Pin on ATWINC3400-MR210CA module	Function
TP101	22	GPIO8; Pin multiplexed with optional BT_UART1_CTS2
TP102	27	GPIO7; Pin multiplexed with optional BT_UART1_RTS2
TP103	29	GPIO17; Pin multiplexed with dual LED D101 (Green)
TP104	30	GPIO18; Pin multiplexed with dual LED D101 (Red)
TP105	31	GPIO19
TP106	32	GPIO20

## **5. Hardware Revision History and Known Issues**

### **5.1 Identifying Product ID and Revision**

The revision and product identifier of the ATWINC3400-XPRO can be found by looking at the sticker on the bottom side of the PCB. The identifier and revision are printed in plain text as A09-nnnn\rr, where nnnn is the identifier and rr is the revision. The label also contains a 10-digit serial number unique to each board.

The product identifier for the ATWINC3400-XPRO is A09-2623.

### **5.2 Revision**

Revision 5 was the initially released revision. Revision 6 is the latest revision, and there are no known issues.

## 6. Document Revision History

Rev A - 11/2017

Section	Changes
Document	<ul style="list-style-type: none"><li>• Updated from Atmel to Microchip template.</li><li>• Previous version is Atmel 42690 revision A.</li></ul>

## The Microchip Web Site

---

Microchip provides online support via our web site at <http://www.microchip.com/>. This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

## Customer Change Notification Service

---

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at <http://www.microchip.com/>. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

## Customer Support

---

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: <http://www.microchip.com/support>

## Microchip Devices Code Protection Feature

---

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.

- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as “unbreakable.”

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip’s code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

## Legal Notice

---

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

## Trademarks

---

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BeaconThings, BitCloud, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq, KeeLoq logo, Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, RightTouch, SAM-BA, SpyNIC, SST, SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BodyCom, chipKIT, chipKIT logo, CodeGuard, CryptoAuthentication, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICKit, PICtail, PureSilicon, QMatrix, RightTouch logo, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2017, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN: 978-1-5224-2405-5

## Quality Management System Certified by DNV

---

### ISO/TS 16949

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC<sup>®</sup> MCUs and dsPIC<sup>®</sup> DSCs, KEELOQ<sup>®</sup> code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.



## Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
<p><b>Corporate Office</b> 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: <a href="http://www.microchip.com/support">http://www.microchip.com/support</a> Web Address: <a href="http://www.microchip.com">www.microchip.com</a></p> <p><b>Atlanta</b> Duluth, GA Tel: 678-957-9614 Fax: 678-957-1455</p> <p><b>Austin, TX</b> Tel: 512-257-3370</p> <p><b>Boston</b> Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088</p> <p><b>Chicago</b> Itasca, IL Tel: 630-285-0071 Fax: 630-285-0075</p> <p><b>Dallas</b> Addison, TX Tel: 972-818-7423 Fax: 972-818-2924</p> <p><b>Detroit</b> Novi, MI Tel: 248-848-4000</p> <p><b>Houston, TX</b> Tel: 281-894-5983</p> <p><b>Indianapolis</b> Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380</p> <p><b>Los Angeles</b> Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800</p> <p><b>Raleigh, NC</b> Tel: 919-844-7510</p> <p><b>New York, NY</b> Tel: 631-435-6000</p> <p><b>San Jose, CA</b> Tel: 408-735-9110 Tel: 408-436-4270</p> <p><b>Canada - Toronto</b> Tel: 905-695-1980 Fax: 905-695-2078</p>	<p><b>Australia - Sydney</b> Tel: 61-2-9868-6733</p> <p><b>China - Beijing</b> Tel: 86-10-8569-7000</p> <p><b>China - Chengdu</b> Tel: 86-28-8665-5511</p> <p><b>China - Chongqing</b> Tel: 86-23-8980-9588</p> <p><b>China - Dongguan</b> Tel: 86-769-8702-9880</p> <p><b>China - Guangzhou</b> Tel: 86-20-8755-8029</p> <p><b>China - Hangzhou</b> Tel: 86-571-8792-8115</p> <p><b>China - Hong Kong SAR</b> Tel: 852-2943-5100</p> <p><b>China - Nanjing</b> Tel: 86-25-8473-2460</p> <p><b>China - Qingdao</b> Tel: 86-532-8502-7355</p> <p><b>China - Shanghai</b> Tel: 86-21-3326-8000</p> <p><b>China - Shenyang</b> Tel: 86-24-2334-2829</p> <p><b>China - Shenzhen</b> Tel: 86-755-8864-2200</p> <p><b>China - Suzhou</b> Tel: 86-186-6233-1526</p> <p><b>China - Wuhan</b> Tel: 86-27-5980-5300</p> <p><b>China - Xian</b> Tel: 86-29-8833-7252</p> <p><b>China - Xiamen</b> Tel: 86-592-2388138</p> <p><b>China - Zhuhai</b> Tel: 86-756-3210040</p>	<p><b>India - Bangalore</b> Tel: 91-80-3090-4444</p> <p><b>India - New Delhi</b> Tel: 91-11-4160-8631</p> <p><b>India - Pune</b> Tel: 91-20-4121-0141</p> <p><b>Japan - Osaka</b> Tel: 81-6-6152-7160</p> <p><b>Japan - Tokyo</b> Tel: 81-3-6880-3770</p> <p><b>Korea - Daegu</b> Tel: 82-53-744-4301</p> <p><b>Korea - Seoul</b> Tel: 82-2-554-7200</p> <p><b>Malaysia - Kuala Lumpur</b> Tel: 60-3-7651-7906</p> <p><b>Malaysia - Penang</b> Tel: 60-4-227-8870</p> <p><b>Philippines - Manila</b> Tel: 63-2-634-9065</p> <p><b>Singapore</b> Tel: 65-6334-8870</p> <p><b>Taiwan - Hsin Chu</b> Tel: 886-3-577-8366</p> <p><b>Taiwan - Kaohsiung</b> Tel: 886-7-213-7830</p> <p><b>Taiwan - Taipei</b> Tel: 886-2-2508-8600</p> <p><b>Thailand - Bangkok</b> Tel: 66-2-694-1351</p> <p><b>Vietnam - Ho Chi Minh</b> Tel: 84-28-5448-2100</p>	<p><b>Austria - Wels</b> Tel: 43-7242-2244-39 Fax: 43-7242-2244-393</p> <p><b>Denmark - Copenhagen</b> Tel: 45-4450-2828 Fax: 45-4485-2829</p> <p><b>Finland - Espoo</b> Tel: 358-9-4520-820</p> <p><b>France - Paris</b> Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79</p> <p><b>Germany - Garching</b> Tel: 49-8931-9700</p> <p><b>Germany - Haan</b> Tel: 49-2129-3766400</p> <p><b>Germany - Heilbronn</b> Tel: 49-7131-67-3636</p> <p><b>Germany - Karlsruhe</b> Tel: 49-721-625370</p> <p><b>Germany - Munich</b> Tel: 49-89-627-144-0 Fax: 49-89-627-144-44</p> <p><b>Germany - Rosenheim</b> Tel: 49-8031-354-560</p> <p><b>Israel - Ra'anana</b> Tel: 972-9-744-7705</p> <p><b>Italy - Milan</b> Tel: 39-0331-742611 Fax: 39-0331-466781</p> <p><b>Italy - Padova</b> Tel: 39-049-7625286</p> <p><b>Netherlands - Drunen</b> Tel: 31-416-690399 Fax: 31-416-690340</p> <p><b>Norway - Trondheim</b> Tel: 47-7289-7561</p> <p><b>Poland - Warsaw</b> Tel: 48-22-3325737</p> <p><b>Romania - Bucharest</b> Tel: 40-21-407-87-50</p> <p><b>Spain - Madrid</b> Tel: 34-91-708-08-90 Fax: 34-91-708-08-91</p> <p><b>Sweden - Gothenberg</b> Tel: 46-31-704-60-40</p> <p><b>Sweden - Stockholm</b> Tel: 46-8-5090-4654</p> <p><b>UK - Wokingham</b> Tel: 44-118-921-5800 Fax: 44-118-921-5820</p>