

- Built-in Li-ion battery
- Microprocessor controller guarantees high reliability
- Auto start when plugged in
- Manual power off switch
- Multi-color indicator
- Overload, short-circuit, over-charge and over-discharge protection



Model	DCEnergy 25
<b>AC INPUT</b>	
Voltage Range	90 VAC ~ 264 VAC
Frequency	50 or 60 Hz
Surge protection	1.5KV (Optional K.21 enhanced, 6KV)
<b>DC OUTPUT</b>	
Voltage	12VDC ± 5%
Max. Power	25W (2.1A)
<b>BATTERY</b>	
Type	Lithium-ion Battery
Voltage	3.7VDC
Capacity	2600mAh
Typical Charging Time	3 hours recover to 90% capacity
<b>PROTECTION</b>	
Battery	Deep Discharge, Over-charge and Short Circuit Protection
Input/Output	Fuse for Short Circuit and Overload Protection
<b>INDICATORS</b>	
LED Display	Full Battery / Green lighting
Battery Charging	Constant flashing on Green LED
Battery Discharging	Quick flashing on Green LED
Fault	Red lighting
<b>PHYSICAL</b>	
Input Plug	Mounted on the housing (NEMA/EU/UK)
Output cable	1m Length (DC Male Jack, OD 4mm, ID 1.7mm)
Dimension, D x W x H (mm)	68 x 42 x 74
Net Weight (g)	280

Product specifications are subject to change without further notice.