

FOAM

HARD FOAM CUSTOM CUSHIONING FOR NEWBOX

NEWBOX TOTE-BOX

Conductive polypropylene Tote-Boxes, stackable, Rs $10^6 \Omega$

Available in two EURO format: 400x300mm and 600x400mm

ANTISTATIC HARD PINK FOAM

Use: cushioning purposes
Density: 20 Kg/m³, Rs $10^{12} \Omega$
7804.165 1m x 1.5m sheet, thickness 10mm
7804.166 1m x 1.5m sheet, thickness 20mm

Newbox



>>> go to page 20



CUSTOM CUT

FOAM (CUSTOM CUT)

ANTISTATIC SOFT PINK FOAM

Use: cushioning purposes
Density: 30 Kg/m³, Rs $10^{12} \Omega$
7804.161 1m x 1.5m sheet, thickness 6mm
7804.162 1m x 1.5m sheet, thickness 10mm

CONDUCTIVE SOFT BLACK FOAM

Use: cushioning purposes
Density: 30 Kg/m³, Rs $10^6 \Omega$
7804.168 1m x 1m sheet, thickness 6mm
7804.170 1m x 1m sheet, thickness 10mm
7806.300 550 x 350mm sheet, thickness 10mm for Euro 600x400 container
7806.306 360 x 260mm sheet, thickness 10mm for Euro 300x400 container

CONDUCTIVE HARD BLACK FOAM

Use: insertion of component leads
Density: 65Kg/m³, Rs $10^5 \Omega$
7804.172 1m x 1m sheet, thickness 6mm
7804.174 1m x 1m sheet, thickness 10mm

CROSS LINKED CONDUCTIVE BLACK FOAM

Use: insertion of component leads high grade, extended life
Density: 60Kg/m³, Rs $10^6 \Omega$
7804.156 1m x 1.78m sheet, thickness 2.5mm
7804.158 1m x 1.78m sheet, thickness 7.5mm



CUSTOM CUT

NOT-ESD MOISTURE BARRIER BAGS

(Packaging of 100pcs)

TEXTURED BARRIER BAGS

In external aspiration appliances textured bags are the best solution for an easy operation. One of the inner layer is made with small straight rails parallel to the lateral sides that facilitate the output of the air during the aspiration job.

embossed inner side



flat inner side

Opening on the short side (mm)	Embossed 85µm	Flat 95µm
150 x 200	6604.004	6603.923
150 x 300	6604.006	6603.925
200 x 300	6604.010	6603.928
250 x 350	6604.015	6603.932
250 x 600	6604.020	6603.936
300 x 400	6604.025	6603.940
400 x 600	6604.030	6603.945
Tubing 200x6m	6604.052	
Tubing 300x6m	6604.054	