
# FLOORS

### **WINYLAR**

VINYLAB is a resilient, permanently static-dissipative control flooring developed for facilities where static discharge may cause damage to sensitive electronic devices.

The VINYLAB mat meets the requirements for floors in standard IEC61340-5-1, the "Combination Resistance" with appropriate shoes is  $35M\Omega$ .

It is made by two vinyl layers, the underside layer is black conductive, the top layer, glare free coloured surface, has a  $1x10^6\Omega$  typical Rs.



## MAT

- It is required a perfect, smooth permanently dry and sound subfloor.
- Never use conductive primers, since they reduce the subfloor's absorbency.
- Rubber mats should be dry laid first to reach the floor temperature (acclimatise)
- Use conductive adhesive to apply the rubber mat.
- Water dispersion adhesive type ECO V4, easy to apply, is mostly used on absorbent and moisture-stable subfloors.
- -Detailed installation procedures available on demand.

7805.820 7805.818 Mat roll, azure colour 140cm x 2.2mm x 10m. Mat roll, grey colour 140cm x 2.2mm x 10m.

INTERLOCKING FLOOR TILE

The tiles are clicked together quickly and can be dry laid over any hard and flat base even on damaged, damp or contaminated surfaces.


To have a reliable ground connection create a copper grid under the tiles and ground it.

Dimensions: 500 x 500 x 4 mm

Weight: 6kg/m<sup>2</sup>

Packages: 20 tiles for package (4.70m<sup>2</sup>)

7805.800 7805.801 Interlocking tile, azure colour Interlocking tile, grey colour





## TECO V4 GLUE FOR MATS, ONE COMPONENT

Conductive glue for sticking mats on benches or on the floor. Rs.:  $< 3x10^5 \Omega$ 

7805.840

One component conductive glue, gray color, 16kg can Useful time 10-15 minutes, consumption about 350g/m<sup>2</sup>

### **TOPPER EARTHING TAPE**

Used to ground ESD matting Self-adhesive - 0.05mm thickness - 30m long roll

7805.828 7805.830 COPPER tape 10mm wide COPPER tape 15mm wide



#### FLOOR GROUNDING KIT AND TEST POINT

#### 7805.834 GROUNDING KIT

Supplied with two meters long copper earthing type. Dowels and screws not supplied.

