


PCB MOUNTING LAYOUT

SPECIFICATION

- (1) ITEM NO. : CH025-1616LF
- (2) HOUSING MATERIAL:PBT UL94V0, BLACK COLOR
- (3) CONTACT 1 MATERIAL:Ø0.8MM SPRING STEEL NICKEL PLATED
CONTACT 2 MATERIAL:0.4MM THICK SPRING STEEL NICKEL PLATED
- (4) CURRENT RATING : 0.5A (AC/DC)
- (5) VOLTAGE RATING : 500V (AC/DC)
- (6) CONTACT RESISTANCE: 30 MILLIOHMS
- (7) INSULATION RESISTANCE: 1000 MEGAOHMS
- (8) TEMPERATURE RANGE: -55° TO +85°
- (9) HUMIDITY: 40° AND 90-95% RH FOR 96 HOURS
- (10)RoHS COMPLIANT

3				
2				
1				
NO.	MODIFICATION	DATE	SCALE	2:1
General Tolerances			UNIT	MM
0 ~ >3	± 0.10	30 ~ >120 ± 0.30	MAT'L	SEE SPEC.
3 ~ >6	± 0.10	120 ~ >400 ± 0.50	DATE	DEC. 10. 2013
6 ~ >30	± 0.20	Angle: ± 3°	 The Third Angle Projection	

SHOGYO INTERNATIONAL CORP.
#CH025-1616LF
 COIN CELL HOLDER