

Part Number: 731000114

Product Description: 50 Ohms, SMA Right-Angle PCB Jack Receptacle, Brass Body, Gold

Plated, Tray

Series Number: 73251

Status: Active

**Product Category:** RF / Coaxial Connectors



#### **Documents & Resources**

#### **Drawings**

Drawing 731000114\_sd.pdf

3D Models and Design Files

3D Model 731000114\_stp.zip 3D Model PDF 731000114.pdf

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>®</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Contains Lead per D(2022)9120-DC<br>(17 Jan 2023) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## **Part Details**

## General

| Status         | Active  |
|----------------|---|
| Category       | RF / Coaxial Connectors   |
| Series         | 73251   |
| Description    | 50 Ohms, SMA Right-Angle PCB Jack<br>Receptacle, Brass Body, Gold<br>Plated, Tray |
| Product Family | SMA RF Connectors   |
| Product Name   | SMA   |
| Style          | РСВ   |
| Туре           | Subminiature  |
| UPC            | 800753686373  |

## Electrical

| Frequency       | 12 GHz                      |
|-----------------|-----------------------------|
| Impedance       | 50Ω                         |
| Power / Voltage | VOLTAGE: 500 Vrms@Sea Level |

# Physical

| Gender                      | Jack         |
|-----------------------------|--------------|
| Keying to Mating Part       | None         |
| Net Weight                  | 2.432/g      |
| Orientation                 | Right Angle  |
| Packaging Type              | Tray         |
| Panel Mount                 | No           |
| Panel Mount Method          | N/A          |
| PCB Mounting                | Through Hole |
| PCB Thickness - Recommended | 3.20mm       |
| Reverse Polar               | No           |
| Wire/Cable Type             | N/A          |

## **Solder Process Data**

| Max-Duration                 | 10       |
|------------------------------|----------|
| Lead-Free Process Capability | SMC&WAVE |
| Max-Cycle                    | 2        |
| Max-Temp                     | 260      |

This document was generated on Sep 01, 2023