




Country of Origin :	China
Operating Temperature :	10 ÷ 40[°C]
Dimension :	135 x 57 x 31[mm]
Suitable cable :	IEC320-C5 ("Mickey Mouse")
Approvals / Marks :	  



### Features:

- Single Output.
- Wide input voltage (100~240)VAC with IEC 320-C6 Inlet.
- High Performance.
- Overload & Short circuit protection.
- For I.T.E. use only + RoHS conform.

### Specification - DESKTOP:

		OUTPUT				
	Model	Voltage DC [V]	Load [A]	Tolerance [%]	Max.Power [W]	DC connector [mm]
	STXX-8412-M3	12	7	5	84	2.1x5.5x11
INPUT	Voltage	(100 ~ 240)VAC				
	Frequency	(47 ~ 63) Hz				
	Current	max. 1.5A				
PROTECTION	Over Load	Yes				
	Short Circuit	Yes				
OTHERS	Startup time	-				
	Protective earthing	Class I.				
Environment	Temperature	(10 ~ 40)°C				
	Humidity	5% ~ 95% RH				
Connection	Input	IEC 320-C5 ("Mickey Mouse")				
	Output	Connector size depends on customer and upon specifications, 1.5m round cable				

### SAFETY

EMC		60950-1:2001 + A11:2004; EN55022:1998/A2:2003; EN55024:1998/A2:2003; EN61000-3-2:2000/A2:2005; EN61000-3-3:1995/A2:2005
WEIGHT		N.W.: 0.37 kg / pc
PACKING	Box	0.48 x 0.33 x 0.39 [m]
		50pcs / 1box
		G.W.: 21 kg / box