



Wire Range	Insulation Diameter	Reel Q'ty
AWG #26~#30	1.35 (.053) MAX.	10,000 PCS.

Ordering Code

$\frac{CI03}{①}$
 $\frac{T01}{②}$
 $\frac{2}{③}$
 $\frac{B}{④}$
 $\frac{P}{⑤}$
 $\frac{H}{⑥}$

- ① Series No.
- ② Type: T01= AWG #26 ~ #30
- ③ Plating: 2= Gold Flash Plated over 0.76μm(30μ") Nickel
- ④ Material: B= Brass
- ⑤ Plating method: P= Post Plating
- ⑥ Option: H= High insertion force (For 02~19 circuits housing)

CVILUX CORP
2016.11.10
ISSUED

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE:	瀚荃股份有限公司 CviLux Corporation
③						TOLERANCE UNLESS OTHERWISE SPECIFIED	CRIMP TERMINAL	
②	Karen	10/05-16'	ECNT116227/ECRT116065	DRAWN BY:	Karen	10/18-16'	MATERIAL:	
①	Sun	12/28-09'	ECR09162-0/ECN09615	ENGINEER:	Sun	10/20-16'	FINISH:	
SYM	NAME	DATE	REVISIONS	CHECKED BY:	Eisley	10/20-16'		DRAWING NO. CI0302SG PART NO. CI03T012BPH
				APPROVED BY:	Eisley	10/20-16'		SCALE 6 / 1 SHEET 1 OF 1