



Material:

Insulator: Glass filled polyester UL 94V-0

Contact: Brass

△ Shell: Steel, Nickel plated as standard

Ordering Code

CD51 25 P A 1 00
① ② ③ ④ ⑤ ⑥

① Series No.

② No. of Circuits: 9,15,25,37

③ Contact type: P= Plug(Male)

△ △ ④ Plating option:

A= Selective Gold flash plated over Nickel

⑤ Color: 1= Black, 7= Blue, 0= White

⑥ Other Option:

00 = With $\phi 3.05$ mm holes on shell(Standard)

A0 = Riveted #4-40 UNC close nuts on front shell

B0 = Riveted #4-40 UNC open nuts on front shell

C0 = Riveted #4-40 UNC open nuts on rear shell

Circuits	Dimension			
	A	B	C	D
9	25.00(.984)	30.8(1.213)	16.92(.666)	19.20(.756)
15	33.32(1.312)	39.2(1.543)	25.25(.994)	27.70(1.091)
25	47.04(1.852)	53.1(2.091)	38.96(1.534)	41.10(1.618)
37	63.50(2.500)	69.4(2.732)	55.42(2.182)	57.30(2.256)



Mounting Style		Lead Free Process		RoHS Compliant			
Code	00	Code	A0	Code	B0	Code	C0
			DIM. L= 5.8mm		DIM. L= 4.0mm		DIM. L= 4.0mm

△7	Ken	3/15-18'	ECRT117079/ECNT118047		DATE	UNIT: mm / inch	SOLDER CUP SERIES	瀚荃股份有限公司 CviLux Corporation
△6	Sandy	3/25-10'	ECN10079	DRAWN BY: Ken	3/15-18'	TOLERANCE UNLESS OTHERWISE SPECIFIED		
△5	Sun	9/30-09'	ECR09128-0/ECN09488	ENGINEER: Sun	3/16-18'	.X ±0.30/.012 X: ± 1'		
△4	Sun	5/16-08'	ECN08225	CHECKED BY: Eisley	3/23-18'	.XX ±0.20/.008 X: ±		
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	3/23-18'	.XXX ±0.10/.004 XX: ±	MATERIAL:	DRAWING NO. CD5101SI
							FINISH:	PART NO. CD51**PA***
							SCALE	SHEET 1 OF 1