



Recommended P.C. Board Layout

Material:
 * Insulation: Nylon 66, Color Nature
 * Contact: Brass
 Circuit Pattern Schedule: See Drawing No: CP0110S*

Ordering Code:

CP-01 3 ** * * 0
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Type of Connector: 3= Straight PCB mount header
- ③ No. of Circuits: See below table
- ④ Plating Code:
 △ 1= 2.54 μ m(100 μ ”) Tin over 1.02 μ m(40 μ ”) Nickel
 2= Gold flash plated over 1.27 μ m(50 μ ”) Nickel
 B= Selective 0.38 μ m(15 μ ”) gold plated over 1.27 μ m(50 μ ”) Nickel
 C= Selective 0.76 μ m(30 μ ”) gold plated over 1.27 μ m(50 μ ”) Nickel
- ⑤ Variation:
 4= UL 94V-2, With mounting pegs
 5= UL 94V-0, With mounting pegs
- ⑥ Other option:
 0= Standard

Halogen-Free
 Tin-Lead Process
 RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: STRAIGHT HEADER	瀚荃股份有限公司 CviLux Corporation			
③					DRAWN BY: Sandy	5/12-08'	CP-01 POWER CONNECTOR				
②					ENGINEER: Easley	5/13-08'	MATERIAL:	DRAWING NO. CP0130SK	PART NO.	CP-013***40	CP-013***50
①	Sandy	5/12-08'	ECN08219		CHECKED BY: David	5/13-08'	FINISH:	SCALE	2 / 1	SHEET	1 OF 1
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	5/13-08'					

CVILUX CORP
 2008.05.13
 ISSUED