



|   |  |   |  |
|---|--|---|--|
| Model: LP603448   |  | Overcharge Detection Voltage(V)   | 4.28±0.05                                    |
| Min. Capacity 最低容量 (mAh)<br>(0.2C, 25±3°C)<br>*Single cell capacity (单体电芯容量)    |  | Overdischarge Detection Voltage(V)  | 2.3±0.1                                      |
| Typical Capacity 典型容量 (mAh)<br>(0.2C, 25±3°C)<br>*Single cell capacity (单体电芯容量) |  | 过放保护电压 (V)  | Limited to Max loading current<br>仅用于最大的负载电流 |
| Nominal Voltage 标称电压 (V)  |  | 峰值 2 (A)  | constant (A)<br>持续 1 (A)                     |
| Internal impedance 内阻 (≅)<br>(m , AC 1KHz)                                      |  | 客户要求最大的负载电流<br>峰值 (A)   | constant (A)<br>持续 (A)                       |
| Charge Temp. 充电温度 (°C)  |  | Customer required Max loading current   |  |
| Discharge Temp. 放电温度 (°C)   |  | If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design.<br>(如果实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用情况对 PCM 的设计至关重要) |  |
| Humidity(湿度)  |  | 65±20%  |  |

|                                     |  |     |  |      |  |     |  |     |  |      |  |         |  |        |  |
|-------------------------------------|--|-----|--|------|--|-----|--|-----|--|------|--|---------|--|--------|--|
| Battery pack specification<br>电池组规格 |  | 950 |  | 1050 |  | 3.7 |  | 200 |  | 0~45 |  | -20~60° |  | 65±20% |  |
| Ambient Conditions<br>(环境温度)        |  | 950 |  | 1050 |  | 3.7 |  | 200 |  | 0~45 |  | -20~60° |  | 65±20% |  |

Remark(备注):  
1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).  
2. Rohs compliant(严格按照ROHS要求生产).

|                        |  |                     |  |             |  |         |  |
|------------------------|--|---------------------|--|-------------|--|---------|--|
| EEMB BATTERY           |  | Drawn: eiyuanchao   |  | Revise No.: |  | E4-2009 |  |
| Title LP603448-PCM-LD/ |  | Checked 1: Tina     |  | Projection: |  | E4-2009 |  |
| File NO. A13151        |  | Checked 2:          |  | Page:       |  | 1/1     |  |
| Draw Date: 2016/9/1    |  | Approved:           |  | Scale:      |  | 1:1     |  |
|                        |  | Draw Date: 2016/9/1 |  | Unit:       |  | mm      |  |