



# PosiLok™ Disposable Dispense Tip Bulk Packed


The dispense tip helps define the deposit shape and the performance of your dispenser.



## Tapered FreeFlow™

**Precision taper** allows fluid to flow without restriction, reducing stringing and ooze. Polypropylene molded with UV light block. These tips feature the PosiLok™ hub.


Gauge	Flexible	Rigid
14G	E415151	E405151
16G	E415131	E405131
18G	E415111	E405111
20G	E415091	E405091
22G	E415071	E405071
25G	E415041	E405041



## Straight but Flexible

**Soft polypropylene** burr and flash free tips assure accurate deposit control. Recommended for use with fluids that react with metals or to prevent scratching.


Gauge	.5" long	1" long
15G	E281141	E283141
18G	E281111	E283111
20G	E281091	E283091
25G	E281041	E283041



## Perfectly Straight Stainless Steel

PosiLok™ polypropylene hub with **polished 304 stainless steel** tubing cut burr free.

Gauge	.5" long	1" long	1.5" long
14G	E011151	E012151	E013151
15G	E011141	E012141	E013141
16G	E011131	E012131	E013131
18G	E011111	E012111	E013111
19G	E011101	E012101	E013101
20G	E011091	E012091	E013091
21G	E011081	E012081	E013081
22G	E011071	E012071	E013071
23G	E011061	E012061	E013061
25G	E011041	E012041	E013041
27G	E011021	E012021	E013021
30G	E011010	N/A	N/A



## Precisely Bent Stainless Steel

PosiLok™ polypropylene hub with polished 304 stainless steel tubing cut burr free. **Bent at 45 and 90 degree** angles.

Gauge	.5" long 45° Angle	.5" long 90° Angle	1.5" long 45° Angle
14G	E501151	E601151	E503151
15G	E501141	E601141	-
16G	E501131	E601131	-
18G	E501111	E601111	E503111
19G	E501101	E601101	-
20G	E501091	E601091	-
21G	E501081	E601081	E503081
22G	E501071	E601071	-
23G	E501061	E601061	-
25G	E501041	E601041	-
27G	E501021	E601021	-
30G	E501010	E601010	-



# PosiLok™ Dispense Tip Bulk Packed



## Microdot

PosiLok™ polypropylene hub with polished 304 stainless steel tubing cut burr free. **Small gauge** designed for microdot dispensing.

Gauge	.25" long	.312" long	Hub Color
27G	–	E01Y021	Clear
30G	–	E01Y011	Lavender
32G	E019411	–	Yellow



## Fine Surface

PosiLok™ polypropylene hub with polished 304 stainless steel tubing cut burr free. **Chamfered** tip reduces surface tension allowing easy deposit of fluid on fine surfaces.

Gauge	.5" long
18G	E341111
23G	E341061
25G	E341041



## Thick Paste

PosiLok™ polypropylene hub with polished 304 stainless steel tubing cut burr free. **.25" length** designed for filled or thick pastes.

Gauge	.25" long
18G	E019111
20G	E019091
21G	E019081



## Teflon® Lined

Teflon® burr and flash free tips assure accurate deposit control. Recommended for use with fluids that **react or bond with metals** such as cyanoacrylates. Prevent scratching.

ID	1/2" long	Color
0.020"	E031081	Grey
0.006"	E031041	Pink



## UV Light Shield

One piece shield slides over the tip blocking light from penetrating the PosiLok™ polypropylene hub. Fits on the end of the syringe ideal for **UV and light sensitive adhesives**.

Barrel Size	Part #	Color
5cc	A560C21	Black
3,10-55cc	A550C21	Black

Color	Gauge	ID Size		OD Size	
		in	mm	in	mm
● White	14G	.063	1.60	.083	2.11
● Brown	15G	.052	1.32	.072	1.83
● Charcoal	16G	.047	1.19	.065	1.65
● Green	18G	.033	.84	.050	1.27
● Lt.Green	19G	.027	.69	.042	1.07
● Pink	20G	.023	.58	.036	.91
● Purple	21G	.020	.51	.032	.81
● Blue	22G	.016	.41	.028	.71
● Orange	23G	.013	.33	.025	.64
● Red	25G	.010	.25	.020	.51
● Gray	27G	.008	.20	.016	.41
● Lavender	30G	.006	.15	.012	.31
● Yellow	32G	.004	.10	.009	.23