



SUNNYWAY

SWE020-RP

PN: SW19050EB56-RP



Sunnyway Technology

Add: Building 65-302, No.421 Hongcao Road, Xuhui District, Shanghai

Tel: +86-021-6484 2326 Fax: +86-021-6484 2328

Email: sales@sunny-way.com Web: www.sunny-way.com

1. Electrical Specifications


Standards	WiFi/BT
Frequency range (MHz)	2400~2500MHz
Peak Gain (dBi)	1.7~3.7dBi
Average Gain (dB)	-2.4~-4.1dB
VSWR	<1.6
Return Loss	<-13.0
Efficiency (%)	39~57%
Polarization mode	Linear
Radiation pattern	Omni-Directional
Output impedance (Ω)	50
Max. Input Power(W)	25

2. Mechanical and Environmental Specification


Mounting Type	Connector Mount
Connector Type	SMA-RP
Antenna size(mm)	47.3mm* ϕ 8.5mm
Material	ABS
Operating Temperature ($^{\circ}\text{C}$)	- 40 $^{\circ}\text{C}$ ~ + 85 $^{\circ}\text{C}$
Storage Temperature($^{\circ}\text{C}$)	- 40 $^{\circ}\text{C}$ ~ + 85 $^{\circ}\text{C}$

3. Antenna parameters

FRE (MHz)	2400	2450	2500
VSWR	1.57	1.48	1.48
Return Loss	-13.08	-14.21	-14.17
Eff (%)	38.29	56.12	56.39
Average Gain(dB)	-4.17	-2.51	-2.49




VSWR




Return Loss

2400.00MHz - 2500.00MHz Gain





2400.00MHz - 2500.00MHz Efficiency





Directional pattern



2400.000MHz



2450.000MHz




2500.000MHz





4. Antenna Drawings



2	SMA	SMA-RP	white	1
1	noumenon	ABS	black	1
Series	Component name	Specification	Color	Quantity