

March, 2011

3M™ Aluminum Foil Tape 3380

Product Description

3M™ Aluminum Foil Tape 3380 is a general purpose aluminum foil tape offering an annealed aluminum foil backing combined with an acrylic pressure sensitive adhesive having an easy release PE coated Kraft liner.

Product Features

- General purpose foil tape
- The low water vapor transmission rate makes these tapes a good sealant
- Low flammability 3M™ Aluminum Foil Tape 3380 is UL 723 approved (File R7311)
- 3M[™] Aluminum Foil Tape 3380 is US Coast Guard approved (CGA #164.112/63/0)
- Best adhesion results attained when applied to clean, dry surfaces above 32°F (0°C).



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Silver		
Total Tape Thickness	0.08 mm	3.25 mil	ASTM D3652
Backing Thickness	0.05 mm	2 mil	ASTM D3652
Backing	Aluminum Foil		
Adhesive	Acrylic		
Liner	PE coated Kraft Liner		
Liner Thickness	0.08 mm	3.1 mil	ASTM D3652

Typical Performance Characteristics

Property	Values		Method	Dwell/Cure Time	Substrate	Notes
180° Peel Adhesion	4.3 N/cm	40 oz/in	ASTM D3330	Initial	Stainless Steel	12 in/min (300 mm/min)
Tensile Strength	17.5 N/cm	10 lb/in	ASTM D3759			
Elongation at Break	ո 4 %		ASTM D3759			

Table continued on next page

Typical Performance Characteristics (continued)

Property	Values		Method	Dwell/Cure Time	Substrate	Notes
Temperat Use Range	ur&4 to 127 °C	-30 to 260 °F				

Handling/Application Information

Application Ideas

- General use aluminum foil tape
- Light reflecting
- Heat shielding
- Moisture barrier
- Thermal conducting

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% relative humidity in the original packaging material.

To obtain best performance, use this product within 24 months from date of manufacture.

Industry Specifications

UL 723 (File R7311) US Coast Guard approved (CGA #164.112/63/0)

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all- 3m-products/~/3M-Aluminum-Foil-Tape-3380? N=5002385+3293191633&rt=rud

Table continued on next page

3M™ Aluminum Foil Tape 3380

References (continued)

Property	Values
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=338

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Aluminum Foil Tape 3380

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



