

JBC CD-B Station

[Ask for a demo](#)



Search



Newly Upgraded! More intuitive and well-connected

This station is suitable for both SMD or THT components.

It uses the T245-A General Purpose Handle the perfect tool for general electronic applications with high power requirements.

This station includes:

- Fast and easy configuration of the station thanks to the 7-key keypad.
- **Cartridge Holder** to store up to four cartridges, as well as **Cartridge Extractor** and **Cable Collector**.
- Connectivity to JBC Fume Extractor (connector RJ12).

It provides the best soldering quality thanks to JBC Most Efficient Soldering System and, additionally, the Sleep & Hibernation Modes help to extend the life of tips.

**Don't believe us?..
TRY IT!**



REFERENCES

CD-1BQF 120 V
CD-2BQF 230 V
CD-9BQF 100 V

PRODUCT COMPOSITION

- 1 CD Soldering Station
- 1 T245-A General Purpose Handle (cartridge not included)

SPECIFICATIONS

Selectable Temperature	90 to 450 °C / 190 to 840 °F
CONNECTIVITY	
USB-B	Software PC / Firmware update
Equipotential bonding	Optional connection to EPA
RJ12 Connector	
Earthing Fuse	F 1.25A
ESD/EOS	
ESD safe	
Tip to ground vol./ resist.	Meets and exceed ANSI/ESD S20.20-2014 IPC J-STD-001F
POWER SUPPLY	
Peak power	130 W - 23.5 V
Ambient operating temp.	10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Compact Stations 170 x 176 x 145 mm / 2.74 kg.
6.69 x 6.93 x 5.71 in / 6.04 lb.

Package 234 x 234 x 258 mm / 3.34 kg.
9.21 x 9.21 x 10.16 in / 7.36 lb.

CONNECTABLES

Compatible tools



T210-A

Precision Handle



T210-PA

Blue Grip Precision Handle



T245-A

General Purpose Handle



T245-GA

General Purpose Handle with reinforced cable



T245-PA

Blue Grip General Purpose Handle

Accessories



CC1001

Cable Collector

Consumables



0012994

Stand for CD