


Order No.: 1940240

Type: FK-MCP 1,5/17-STF-3,5

Plug component, Push-in spring connection



The figure shows a 10-position version of the product

## 1 Main features



- |                           |                           |                        |                     |
|---------------------------|---------------------------|------------------------|---------------------|
| • No. of pos.             | 17                        | • Nominal current      | 8 A                 |
| • Conductor cross section | 1.5 mm <sup>2</sup>       | • Nominal voltage      | 160 V               |
| • Color                   | green                     | • Connection direction | 0 °                 |
| • Pitch                   | 3.5 mm                    | • Type of packaging    | packed in cardboard |
| • Connection method       | Push-in spring connection |                        |                     |

## 2 Your advantages

- ✓ Time saving push-in connection, tools not required
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Intuitive use through colour coded actuation lever
- ✓ Screwable flange for superior mechanical stability
- ✓ Quick and convenient testing using integrated test option




Make sure you always use the latest documentation.  
It can be downloaded at: [phoenixcontact.net/product/1940240](https://phoenixcontact.net/product/1940240)

**1940240 FK-MCP 1,5/17-STF-3,5****3 Table of contents**

1	Main features.....	1
2	Your advantages .....	1
3	Table of contents .....	2
4	3D model in PDF can be activated (Acrobat Reader only).....	3
5	item properties.....	4
	5.1 Connection capacity .....	4
	5.2 Material data .....	4
6	Dimensions.....	4
	6.1 Dimensions for the product .....	4
7	Series drawing.....	5
8	Packaging information .....	5
9	Application.....	5
	9.1 Temperature limit values .....	5
10	Mechanical tests.....	6
	10.1 Termination and connection method.....	6
	10.2 Pull-out test .....	6
11	Electrical tests .....	7
	11.1 Electrical data .....	7
	11.2 Air and creepage distances .....	7
	11.3 Electrical function .....	7
	11.4 Temperature cycles.....	7
12	Current carrying capacity/derating curves .....	8
13	Environmental and durability tests .....	9
	13.1 Vibration test .....	9
14	Classification for connectors.....	9
15	Approvals .....	9
16	Commercial Data.....	10
17	corresponding headers.....	10
18	Accessories.....	10
19	Combination tests.....	11

1940240 FK-MCP 1,5/17-STF-3,5

4 3D model in PDF can be activated (Acrobat Reader only)



**1940240 FK-MCP 1,5/17-STF-3,5****5 item properties**

Order No.	1940240
Type	FK-MCP 1,5/17-STF-3,5
Type of contact	Female connector
Range of articles	FK-MCP 1,5/...-STF
Pitch	3.5 mm
Number of positions	17
Connection method	Push-in spring connection
Locking	Screw flange

**5.1 Connection capacity**

Conductor cross section, solid	0.14 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Conductor cross section, flexible	0.14 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil	26 to 16
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Conductor cross section flexible, with ferrule with plastic sleeve	0.25 mm <sup>2</sup> to 0.5 mm <sup>2</sup>
Cylindrical gauge a x b / diameter	2.0 mm x 1.2 mm / -
Stripping length	9 mm

**5.2 Material data**

<b>Material of metal parts</b>		
Note	WEEE/RoHS-compliant, whisker-free acc. to IEC 60068-2-82/JEDEC JESD 201	
Contact material	Cu alloy	
Terminal point surface	Sn 4 µm ... 8 µm	
Surface contact area	Sn 4 µm ... 8 µm	
Surface characteristics	hot-dip tin-plated	
<b>Insulating material data</b>	<b>Housing</b>	<b>Actuation element</b>
Insulating material	PA	POM
CTI according to IEC 60112	600	600
Flammability rating according to UL 94	V0	HB
Color	green (6021)	orange (2003)
Glow wire flammability index GWFI according to EN 60695-2-12	850	
Glow wire ignition temperature GWIT according to EN 60695-2-13	775	
Temperature for the ball pressure test according to EN 60695-10-2	125 °C	

**6 Dimensions****6.1 Dimensions for the product**

Length	20.8 mm
Width	69.8 mm
Total height	12.4 mm
Dimension a	56 mm

**1940240 FK-MCP 1,5/17-STF-3,5****7 Series drawing****8 Packaging information**

Type of packaging	packed in cardboard
Pieces per package	50

**9 Application****9.1 Temperature limit values**

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C (dependent on the derating curve)

**1940240 FK-MCP 1,5/17-STF-3,5****10 Mechanical tests**

Mechanical test group A	
Specification	IEC 61984:2008-10
Visual test	Test passed
Specification	IEC 60512-1-1:2002-02
Dimensional test	Test passed
Specification	IEC 60512-1-2:2002-02
Resistance of marking	Test passed
Specification	IEC 60068-2-70:1995-12
Insertion and withdrawal force	Test passed
Specification	IEC 60512-13-2:2006-02
No. of cycles	25
Insertion strength per pos. approx.	7 N
Withdraw strength per pos. approx.	5 N
Polarization and coding	Test passed
Specification	IEC 60512-13-5:2006-02
Test force	20 N
Contact retention in insert	Test passed
Specification	IEC 60512-15-1:2008-05
Test force per pos.	26 N

**10.1 Termination and connection method**

Specification	IEC 60999-1:1999-11
Conductor connection	Test passed
Repeated connection and disconnection	Test passed
Check for damage to conductor or loosening	Test passed

**10.2 Pull-out test**

Termination and connection method: pull-out test	
Specification	IEC 60999-1:1999-11
Result	Test passed
Conductor cross section/conductor type/tractive force actual value	0.14 mm <sup>2</sup> / solid / > 10 N
Conductor cross section/conductor type/tractive force actual value	0.14 mm <sup>2</sup> / stranded / > 10 N
Conductor cross section/conductor type/tractive force actual value	1.5 mm <sup>2</sup> / solid / > 40 N
Conductor cross section/conductor type/tractive force actual value	1.5 mm <sup>2</sup> / stranded / > 40 N
Conductor cross section/conductor type/tractive force actual value	AWG 26 / stranded / > 10 N

**1940240 FK-MCP 1,5/17-STF-3,5****11 Electrical tests****11.1 Electrical data**

Rated current / conductor cross section	8 A / 1.5 mm <sup>2</sup>
Rated insulation voltage (III/2)	160 V
Rated surge voltage (III/2)	2.5 kV
Contact resistance	2 mΩ
Degree of pollution	2

**11.2 Air and creepage distances**

Component	Plug component		
Specification	IEC 60664-1:2007-04		
Mains type	unearthed mains		
Insulating material group	I		
Comparative tracking index (IEC 60112:2003-01)	CTI 600		
Rated insulation voltage	160 V	160 V	320 V
Rated surge voltage	2.5 kV	2.5 kV	2.5 kV
Degree of pollution	3	2	2
Overvoltage category	III	III	II
Minimum clearance case A (inhomogeneous field)	1.5 mm	1.5 mm	1.5 mm
Minimum value of the creepage path requirement in acc. with table	2 mm	1.5 mm	1.6 mm

**11.3 Electrical function**

Specification	IEC 60999-1:1999-11
Result	Test passed
Voltage drop	Voltage drop (U) after the load ≤ 15 mV
Test current (minimum cross section)	4 A DC
Test current (maximum cross section)	8 A DC
Conductor cross section, flexible	0.14 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Conductor cross section, solid	0.14 mm <sup>2</sup> to 1.5 mm <sup>2</sup>

**11.4 Temperature cycles**


Specification	IEC 60999-1:1999-11
Result	Test passed
Voltage drop	Voltage drop (U) after the load ≤ 22.5 mV or 1.5 x U <sub>after 24 h</sub> The small value is to be used.
Test current (minimum cross section)	4 A DC
Test current (maximum cross section)	8 A DC
Temperature cycles	192
Conductor cross section, flexible	0.14 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Conductor cross section, solid	0.14 mm <sup>2</sup> to 1.5 mm <sup>2</sup>

## 1940240 FK-MCP 1,5/17-STF-3,5

## 12 Current carrying capacity/derating curves

Specification	IEC 61984:2008-10
Note	Representation based on IEC 60512-5-2:2002-02
Reduction factor	0.8
Number of positions	See diagram
Conductor cross section	1.5 mm <sup>2</sup>

## Type: FK-MCP 1,5/...-STF-3,5 with MC 1,5/...-GF-3,5



## Type: FK-MCP 1,5/...-STF-3,5 with MCV 1,5/...-GF-3,5 P...THR

90710\_1000\_en







**1940240 FK-MCP 1,5/17-STF-3,5****13 Environmental and durability tests****13.1 Vibration test**

Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Acceleration	5 g (60.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

**14 Classification for connectors**

Specification	IEC 61984:2008-10
Main features	Connectors without switching capacity (COC)
Construction form	Fixed connectors
Strain relief elements	without strain relief
Connection method	Can be reconnected
Protection against electric shock	Not encapsulated - touch-proof when inserted
Protective conductor	without PE
Lock	no
Connection method	Screwless terminal points

**15 Approvals**

VDE Gutachten mit Fertigungsüberwachung 	
mm <sup>2</sup> /AWG/kcmil	0.2-1.5
Voltage	160 V
Current	8 A
IECEE CB Scheme 	
mm <sup>2</sup> /AWG/kcmil	0.2-1.5
Voltage	160 V
Current	8 A
CCA	
mm <sup>2</sup> /AWG/kcmil	0.2-1.5
Voltage	160 V
Current	8 A
cULus Recognized 	
Use group	B
mm <sup>2</sup> /AWG/kcmil	28-16
Voltage	300 V
Current	8 A
EAC 	

**1940240 FK-MCP 1,5/17-STF-3,5****16 Commercial Data**

Order No.	1940240
Type	FK-MCP 1,5/17-STF-3,5
Pieces per package	50
Net weight	15.169 g
GTIN	4017918877477
	Information that applies locally, see link on page 1
Country of origin	Information that applies locally, see link on page 1

**17 corresponding headers**


Order No.	Type
1843376	MCV 1,5/17-GF-3,5
1843949	MC 1,5/17-GF-3,5

**18 Accessories**


Description	Order No.	Type
Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip	1205037	SZS 0,4X2,5 VDE
	0803883	SK U/2,8 WH:UNBEDRUCKT
	0804073	SK 3,5/2,8:FORTL.ZAHLEN
	1944372	MPS-MT 1-S
Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm <sup>2</sup> ... 6.0 mm <sup>2</sup> , lateral entry, trapezoidal crimp	1212034	CRIMPFOX 6

## 1940240 FK-MCP 1,5/17-STF-3,5


## 19 Combination tests



FK-MCP 1,5/17-STF



MC 1,5/17-GF



MCV 1,5/17-GF-THR

Specification	IEC 61984	IEC 61984		
<b>Mechanical tests (A)</b>				
Insertion/withdrawal force per position	approx. 7 N / 5 N	approx. 16 N / 12 N		
Polarization when inserted Requirement >20 N	Test passed	Test passed		
Contact holder in insert Requirements >20 N	Test passed	Test passed		
<b>Durability tests (B)</b>				
Contact resistance R <sub>1</sub>	2 mΩ	1.4 mΩ		
Insertion/withdrawal cycles	25	25		
Contact resistance R <sub>2</sub>	2.2 mΩ	1.4 mΩ		
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	2.95 kV	2.95 kV		
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	1.39 kV	1.39 kV		
Insulation resistance Requirements > 5 MΩ	10 <sup>12</sup> Ω	> 0.2 TΩ		
<b>Thermal tests (C)</b>				
Tested number of positions	20	12		
Tested conductor cross section	1.5 mm <sup>2</sup>	1.5 mm <sup>2</sup>		
Test current	8 A DC	8 A		
Upper limiting temperature Requirements < 100°C	Test passed	Test passed		
<b>Climatic tests (D)</b>				
Test sequence 1: low temperature storage	-40 °C/2 h	-40 °C/2 h		
Test sequence 2: heat storage	100 °C/168 h	100 °C/168 h		
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle	0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle		
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	2.95 kV	2.95 kV		
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	1.39 kV	1.39 kV		
<b>Environmental and endurance tests (E)</b>				
Specification	IEC 61984:2008-10	IEC 61984:2008-10		
Degree of protection	Finger safety with IP20 test finger	Finger safety with IP20 test finger		