

Lead free Anti oxidant pellets



Technical data AO pellets LF

Ver: 1.6, 12--06 latest version on www.interflux.com

Page 1

Lead free anti oxidant pellets

Description:

Pure tin (Sn) pellets containing an anti oxidant. These pellets allow to dose easily the right quantity of anti oxidant necessary into your solder bath from a low temperature of 235°C and/ or high temperatures from 380°C up to 500°C.

Available for all lead free alloys ▶ green label

Also available for SnPb alloys ▶ blue label



More information:

Packaging

2

Physical properties

Composition A solder alloy containing a concentrated anti-oxidant

Form and odour White silver alloy, inodorous

Specific gravity at 20°C 7,3 g/cc

Content of tin, Sn 100%

Melting point range 232°C

Solubility in water Not soluble

• Better through hole wetting on top side

mation

Key advantages:Dramatic reduction of solder dross for-

 Reducing alloy oxide skin

Lowers solder bar consumption



Technical data AO pellets LF

Page 2



| Packag | ina | | | | | | | | |
|---|--|---|--|--|--|---|--|--|--|
| | ing ately 50 ant gram in plast | | el- | | | | | | |
| guarantee the ucts should m without such. Product inform different conditions. | e applicability or make their own to warranty, either of mation in other Eurlitions under which of our products in | the accuracy of the accuracy of the determine the accuracy of | f this informate the suitabilided. s can be obtained and our prodiction. Users of o | tion or the s ty of each such ed at Interflux [®] I ucts may be use ur products sho | uitability of oh product for the product for the product for the product of the p | i s information and ur products in a their particular p 9042 Gent. Becaus arantee the applicat own tests to determ warranty, either ex | any given situatiourposes. The poses. The poses is the pose we cannot anticolity or the accuration the suitability | ion. Users of or product discussed cipate or control to acy of this informa- of each such prod | ur prod- d is sold he many ation or |
| | | | | | | | | | |

Copyright:

INTERFLUX® ELECTRONICS

For the latest version of this document please consult:

www.interflux.com