

KASCHKE ELEKTRONIK GMBH zertif. nach ISO 9001

Technical Data Sheet

Customer:	Part designation:	Customer part no.:
Kaschke Göttingen	**SP-E 20/6**	**SKNY267-5-24-14**





Core / material / air gap / AL	**E20/6 K2006 or equiv**	
Nominal inductance	**LI = 1,90 mH ± 10%**	
maximum transmissible power	**14W (TNY267 univ.)**	
Working frequency	**132 kHz**	
Transformation ratio	**93:5:18**	
dielctric strength (50Hz/2s)	**WI-WII/WIII = 3,75 KVeff/50Hz**	
Nominal Current		
Design in comp. with standard	**EN61558**	
Working / storage temperature	**-25°C- 115°C**	**-25°C- 85°C**
Miscellaneous	**F (DIN 40040)**	

Remarks : **a.) marking**

Measuring device of L: **W&K 3245** | Measuring conditions of L: **50 mV/10 KHz**

Measured quantity	Unit	No. 1	No. 2	No. 3	No. 4	No. 5

Responsible person:	Date:	Design regulation no:	Index:
Uwe Dickhut	**. .**	**094.944**	**00**

PLEASE GIVE US YOUR WRITTEN RELEASE Date: _____ Signature: _____