


Filotec

Filotec enclosures with membrane keypad area (1.5 mm)



F 1048-220

Order no.: 97118220

* = Available on request.

Characteristics

Protection class

IP 40

Enclosure Material

Al Mg Si 0.5 anodised; for details, please see Technical Information

Scope of delivery

2 enclosure half shells, 8 screws for mounting cover

Note

C = profile length, special lengths on request. Covers: See following pages. Please order separately.

** = supplied without screw accessory pack. Please order fixing screws (1 piece) separately: 59000175.

Dimensions

Dimensions

105 x 48 x 220 mm

Product drawing

[97118220_F-1048-220.pdf](#)

Important!

To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a pressure compensation element.

» Additional information

Technical documentation / Downloads

Technical drawings

3D product data in STEP format: 97118220 F1048-220.stp (874.3 KB)
Drawing for mechanical processing: 97118220 F-1048-220-G.dxf (681.4 KB)

Milling contours are shown here as a DXF file. (Sub D, USB, HDMI, cable glands, ...)

Product drawing in PDF format: 97118220 F-1048-220.pdf (156.2 KB)
Product drawing in DXF format: 97118220 F-1048-220.dxf (1.0 MB)

Product information

Filotec GB.pdf (511.3 KB)

Matching accessories



Cover, natural-coloured anodised aluminium, 2 mm

97610480 F 1048 D

For F 1048-...