

# Alu-Topline

Enclosure profiles, horizontally-divided



ATPH 1865-0300

Order no.: 92865300

\* = Available on request.

## Characteristics

Colour of enclosure group

Natural-coloured anodised

Protection class

IP 54

Enclosure Material

Extruded profiles: Al Mg Si 0.5 anodised; plastic lid: ABS; for details see Technical Information

Scope of delivery

Enclosure profile, 2 parts

Note

Upgradable to IP 54 by fitting AT...DI.

Special lengths on request.

## Important!

To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a pressure compensation element.

» Additional information

## Technical documentation / Downloads

Technical drawings

Product information

## Dimensions

Dimensions

181.2 x 68.2 x 300 mm

Product drawing

[92865300\\_ATPH-1865-0300.pdf](#)

3D product data in STEP format: 92865300 ATPH1865-0300.stp (900.4 KB)

Alu-Topline GB.pdf (1.5 MB)

Drawing for mechanical processing: 92865300 ATPH-1865-0300-G.dxf (422.8 KB)

Milling contours are shown here as a DXF file. (Sub D, USB, HDMI, cable glands, ...)

Product drawing in PDF format: 92865300 ATPH-1865-0300.pdf (42.0 KB)

Product drawing in DXF format: 92865300 ATPH-1865-0300.dxf (497.0 KB)

## Matching accessories

---



### Self-adhesive rubber feet, black

84006700 AB - GF

Polyurethane, 65-75 Shore

Black



### End cover

92065024 ATD 1865-7024

For ATPH 1865

Graphite grey

92065005 ATD 1865-9005

For ATPH 1865

Black



### Seals for ingress protection IP 54

92065000 AT 1865 DI

For ATPH 1865



### Wall fastening, aluminium

92800300 AT 1800-0300 WB

For ATPH ....-0300



### Universal wall fitting

92830024 AT 0300-7024 UWB

For ATPH ....-0300

Graphite grey



### Insulating strip for PCB mounting on the profile

92000100 AT-IS 00020

Length: 101,5 mm