

Alu-Topline

Enclosure profiles, horizontally-divided



ATPH 1865-0150

Order no.: 92865150

* = Available on request.

Characteristics

Colour of enclosure group

Natural-coloured anodised

Protection class

IP 54

Enclosure Material

Extruded profiles: Al Mg Si 0.5 anodised; plastic lid: ABS; for details see Technical Information

Scope of delivery

Enclosure profile, 2 parts

Note

Upgradable to IP 54 by fitting AT...DI.

Special lengths on request.

Important!

To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a pressure compensation element.

» Additional information

Technical documentation / Downloads

Technical drawings

Product information

Dimensions

Dimensions

181.2 x 68.2 x 150 mm

Product drawing

[92865150_ATPH-1865-0150.pdf](#)

3D product data in STEP format: 92865150 ATPH1865-0150.stp (899.8 KB)

Alu-Topline GB.pdf (1.5 MB)

Drawing for mechanical processing: 92865150 ATPH-1865-0150-G.dxf (425.4 KB)

Milling contours are shown here as a DXF file. (Sub D, USB, HDMI, cable glands, ...)

Product drawing in PDF format: 92865150 ATPH-1865-0150.pdf (42.0 KB)

Product drawing in DXF format: 92865150 ATPH-1865-0150.dxf (497.0 KB)

Matching accessories



Self-adhesive rubber feet, black

84006700 AB - GF

Polyurethane, 65-75 Shore

Black



End cover

92065024 ATD 1865-7024

For ATPH 1865

Graphite grey

92065005 ATD 1865-9005

For ATPH 1865

Black



Seals for ingress protection IP 54

92065000 AT 1865 DI

For ATPH 1865



Wall fastening, aluminium

92800150 AT 1800-0150 WB

For ATPH-0150



Universal wall fitting

92815024 AT 0150-7024 UWB

For ATPH-0150

Graphite grey



Insulating strip for PCB mounting on the profile

92000100 AT-IS 00020

Length: 101,5 mm