

# FI-XC3B-1-15000

## Product Details

<b>Part Number</b>	<b>FI-XC3B-1-15000</b>
<b>Status</b>	<b>Active</b>
<b>Features</b>	1.0mm pitch, for interface of LCD, Cable side contacts
<b>Number of Positions</b>	-
<b>Contact Pitch (mm)</b>	
<b>Connector Type</b>	Cable side contacts
<b>Connector Style</b>	
<b>Wire Termination Style</b>	Crimp
<b>PCB Mounting Method</b>	
<b>Applicable Wire</b>	Discrete wire
<b>Applicable Wire Size</b>	
<b>Applicable Wire Insulation Diameter (mm)</b>	0.45 to 0.75
<b>Remarks on Applicable Wire</b>	
<b>Material of Contact</b>	Copper alloy
<b>Finish of Contact in Connecting Area</b>	Gold plating over Nickel
<b>Finish of Contact in Terminal Area</b>	Tin plating over Nickel
<b>Finish of Contact in PCB Mounting Area</b>	
<b>Shell, Material/ Finish</b>	
<b>Material of Housing</b>	

<b>Locking Feature</b>	-
<b>PCB Mounted Height (mm)</b>	-
<b>Applicable Contacts</b>	-
<b>Applicable Product Part Numbers</b>	FI-X30HL, FI-X30HL-B
<b>Packaging Type</b>	Magazine assembly
<b>Quantity in The Standard Packaging (pieces)</b>	15,000 pieces/reel
<b>Documents</b>	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"> <a href="#">Drawings</a> </div> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"> <a href="#">PDF Download</a> </div> </div>
<b>Stock Search</b>	<div style="border: 1px solid #ccc; padding: 5px; display: inline-block;"> <a href="#">Stock Search</a> &gt; </div>
<b>RoHS compliant</b>	10 substances (2011/65/EU)
<b>REACH compliant</b>	211 substances (19/01/2021)
<b>Environment Information</b>	<div style="border: 1px solid #ccc; padding: 5px; display: inline-block;"> <a href="#">RoHS/Reach Certificate</a> &gt; </div>
<b>Remarks</b>	

### Notice

1. The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.  
For purchase, a product specification must be agreed upon.
2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
3. The products presented in this web site are designed for the uses recommended below.

We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

\* Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

\* We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

This site uses cookies to improve its performance, enhance your user experience and tailor advertising. By using this site you consent to the use of cookies as described in our usage policy unless you have changed your cookie settings. Please click [here](#) for more information.

Accept and Hide This Message