

LINNEA-GC2-60

~60° wide beam

SPECIFICATION:

| | |
|----------------|-----------------|
| Dimensions | 283.6 x 43.0 mm |
| Height | 15.2 mm |
| Fastening | clips |
| ROHS compliant | yes ⓘ |



MATERIALS:

| Component | Type | Material | Colour | Finish |
|---------------|-------------|----------|--------|--------|
| LINNEA-GC2-60 | Linear lens | PMMA | clear | |

ORDERING INFORMATION:

| Component | Qty in box | MOQ | MPQ | Box weight (kg) |
|--|------------|-----|-----|-----------------|
| F17166_LINNEA-GC2-60 » Box size: 398 x 298 x 265 mm | 120 | 32 | 8 | 8.2 |






See also our general installation guide: www.ledil.com/installation_guide









OPTICAL RESULTS (MEASURED):

TRIDONIC





LED LLE 24x280mm 1250lm HV HO ADV1
FWHM / FWTM 56.0 + 51.5° / 96.0 + 111.5°
Efficiency 90 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:







OPTICAL RESULTS (SIMULATED):

| | |
|--|---|
| <p> bridgelux</p> <p>LED: Bridgelux SMD 2835</p> <p>FWHM / FWTM: 54.0 + 48.0° / 91.0 + 86.0°</p> <p>Efficiency: 89 %</p> <p>Peak intensity: 1.1 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> |  |
| <p> CREE LEDs</p> <p>LED: J Series 2835</p> <p>FWHM / FWTM: 56.0 + 50.0° / 94.0 + 90.0°</p> <p>Efficiency: 91 %</p> <p>Peak intensity: 0.9 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> |  |
| <p> CREE LEDs</p> <p>LED: J Series 3030</p> <p>FWHM / FWTM: 54.0 + 50.0° / 92.0 + 90.0°</p> <p>Efficiency: 91 %</p> <p>Peak intensity: 1 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> |  |
| <p> LUMILEDS</p> <p>LED: LUXEON 2835 Line</p> <p>FWHM / FWTM: 61.0 + 66.0° / 106.0 + 130.0°</p> <p>Efficiency: 89 %</p> <p>Peak intensity: 0.7 cd/lm</p> <p>LEDs/each optic: 2</p> <p>Light colour: White</p> <p>Required components:</p> |  |

OPTICAL RESULTS (SIMULATED):

| | |
|--|---|
| <p>LUMILEDS</p> <p>LED: LUXEON 3030 HE Plus</p> <p>FWHM / FWTM: 56.0 + 51.0° / 94.0 + 91.0°</p> <p>Efficiency: 90 %</p> <p>Peak intensity: 0.9 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> |  |
| <p>NICHIA</p> <p>LED: NF2W585AR-P8</p> <p>FWHM / FWTM: 59.0 + 54.0° / 98.0 + 105.0°</p> <p>Efficiency: 92 %</p> <p>Peak intensity: 0.9 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> |  |
| <p>NICHIA</p> <p>LED: NF2W757G-MT (Tunable White)</p> <p>FWHM / FWTM: 56.0 + 52.0° / 95.0 + 98.0°</p> <p>Efficiency: 92 %</p> <p>Peak intensity: 0.9 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: Tunable White</p> <p>Required components:</p> |  |
| <p>NICHIA</p> <p>LED: NFSW757H</p> <p>FWHM / FWTM: 58.0 + 52.0° / 96.0 + 92.0°</p> <p>Efficiency: 91 %</p> <p>Peak intensity: 0.9 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> |  |

OPTICAL RESULTS (SIMULATED):


| | |
|---|---|
| <p>NICHIA</p> <p>LED NFSx757G</p> <p>FWHM / FWTM 57.0 + 50.0° / 93.0 + 92.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 0.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> |  |
| <p>OSRAM Opto Semiconductors</p> <p>LED Duris E 2835</p> <p>FWHM / FWTM 58.0 + 51.0° / 94.0 + 89.0°</p> <p>Efficiency 90 %</p> <p>Peak intensity 0.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> |  |
| <p>OSRAM Opto Semiconductors</p> <p>LED Duris S5 (2 chip)</p> <p>FWHM / FWTM 56.0 + 50.0° / 92.0 + 89.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 0.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> |  |
| <p>OSRAM Opto Semiconductors</p> <p>LED OSCONIQ C 2424</p> <p>FWHM / FWTM 56.0 + 50.0° / 92.0 + 87.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> |  |

OPTICAL RESULTS (SIMULATED):

OSRAM


Opto Semiconductors

LED SYNIOS S2222
 FWHM / FWTM 56.0 + 50.0° / 92.0 + 86.0°
 Efficiency 90 %
 Peak intensity 1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LM28xB Series
 FWHM / FWTM 56.0 + 50.0° / 92.0 + 90.0°
 Efficiency 89 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LM301B
 FWHM / FWTM 58.0 + 52.0° / 94.0 + 92.0°
 Efficiency 91 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG


LED LM301D
 FWHM / FWTM 56.0 + 50.0° / 94.0 + 95.0°
 Efficiency 90 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):

SAMSUNG

| | |
|----------------------|-----------------------------|
| LED | LM301Z Plus |
| FWHM / FWTM | 56.0 + 50.0° / 92.0 + 88.0° |
| Efficiency | 89 % |
| Peak intensity | 0.9 cd/lm |
| LEDs/each optic | 1 |
| Light colour | White |
| Required components: | |



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)