



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 4. BERYLLIUM COPPER PER QQ-C-530
- 5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 6. TEFLON MIL-P-19468

9	COVER	NOTE 2	NOTE 3	1	CV-523X06-T
8	INSULATOR	NOTE 6	NATURAL	1	SMA5072A2-9T-50
7	CONTACT PIN	NOTE 4	NOTE 5	1	SMA5990-8
6	GASKET	SILICONE	RED	1	GS-6/43X06
5	RETAINER RING	NOTE 4	NATURAL	1	SMA5000-4-B
4	CONTACT PIN	NOTE 1	NOTE 5	1	SMA1112A4-4-B
3	INSULATOR	NOTE 6	NATURAL	1	SMA1112A3-3T-50
2	HOUSING WITH BODY	NOTE 1	NOTE 3	1	SMA5072A2-2S-B
1	SHELL	NOTE 1	NOTE 3	1	SMA5000-1-C
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS				PART NO.	SMA5072A2-3GT50G-50
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED	DATE
					10-11-01'
				CHECKED	DATE
					10-11-01'
				DRAWN	DATE
					10-11-01'
SCALE	5/1	ISSUE	A	FILE NO	

Amphenol	
TITLE SMA MALE TO FEMALE R/A ADAPTOR	
DRAWING NO. KJ-SMA5072A2-3GT50G-50	
ITEM NO.	