

SPORT-2X2-S1-HT

~10° spot beam. Variant from High Temperature PMMA.

SPECIFICATION:

Dimensions	50.0 x 50.0 mm
Height	16 mm
Fastening	screw
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish	Length
SPORT-2X2-S1-HT	Multi-lens	HT-PMMA	clear		50.0

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C18293_SPORT-2X2-S1-HT » Box size: 480 x 280 x 300 mm	512	128	32	10.9



See also our general installation guide: www.ledil.com/installation_guide


OPTICAL RESULTS (SIMULATED):



LED XP-G2 HE
FWHM / FWTM 10.0° / 20.0°
Efficiency 91 %
Peak intensity 23.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:


Protective plate, glass

Light distribution files




LED XP-G2 HE
FWHM / FWTM 8.0° / 18.0°
Efficiency 95 %
Peak intensity 28.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files



LED XP-G3
FWHM / FWTM 10.0° / 22.0°
Efficiency 95 %
Peak intensity 17.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XP-L HI
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 87 %
 Peak intensity 22.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files




LED XP-L HI
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 95 %
 Peak intensity 24.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




LED LUXEON 5050 Round LES
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 95 %
 Peak intensity 7.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



OPTICAL RESULTS (SIMULATED):




LED LUXEON HL2X
FWHM / FWTM 10.0° / 22.0°
Efficiency 94 %
Peak intensity 20.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED SST-40
FWHM / FWTM 12.0° / 28.0°
Efficiency 95 %
Peak intensity 12.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED NV4WB35AM
FWHM / FWTM 14.0° / 28.0°
Efficiency 96 %
Peak intensity 11.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files


OPTICAL RESULTS (SIMULATED):



LED NVSW219F
FWHM / FWTM 10.0° / 22.0°
Efficiency 95 %
Peak intensity 20.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




LED OSCONIQ P 3737 (3W version)
FWHM / FWTM 12.0° / 24.0°
Efficiency 95 %
Peak intensity 15.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED LH351B
FWHM / FWTM 10.0° / 22.0°
Efficiency 95 %
Peak intensity 19.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)