

## TINA-D

~16° diffused spot beam optimized for CREE  
XP-E

## SPECIFICATION:

Dimensions	Ø 16.1
Height	9.7 mm
Fastening	tape
ROHS compliant	yes ⓘ




## MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
TINA-D	Single lens	PMMA	clear		
TINA-XP-H-TAPE-WHT	Holder	PC	white		
TINA-TAPE3	Tape	Acryl tape	black		

## ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
FA10644_TINA-D » Box size: 470 x 240 x 105 mm	2016	288	144	4.2



See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

## OPTICAL RESULTS (MEASURED):



LED XP-E  
FWHM / FWTM 14.0° / 29.0°  
Efficiency 93 %  
Peak intensity 9.6 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files




LED XP-G  
FWHM / FWTM 20.0° / 40.0°  
Efficiency 93 %  
Peak intensity 5.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files



LED XT-E  
FWHM / FWTM 17.0° / 35.0°  
Efficiency 94 %  
Peak intensity 6.2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:





Light distribution files

#### OPTICAL RESULTS (MEASURED):



LED LUXEON 2835 Architectural  
 FWHM / FWTM 17.0° / 38.0°  
 Efficiency 96 %  
 Peak intensity 6.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED Z5  
 FWHM / FWTM 12.0°  
 Efficiency %  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:

Light distribution files



LED Z5M1/Z5M2  
 FWHM / FWTM 16.0° / 34.0°  
 Efficiency 94 %  
 Peak intensity 7.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:





Light distribution files

### OPTICAL RESULTS (MEASURED):

**TOSHIBA**  
Leading Innovation >>>

LED TL1L4  
FWHM / FWTM 17.0° / 36.0°  
Efficiency 94 %  
Peak intensity 6.6 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED NCSWE13A  
FWHM / FWTM 12.0° / 24.0°  
Efficiency 89 %  
Peak intensity 14.2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED NVSxE21A  
FWHM / FWTM 14.0° / 30.0°  
Efficiency 93 %  
Peak intensity 10.5 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED NVSxx19B/NVSxx19C  
FWHM / FWTM 18.0° / 34.0°  
Efficiency 88 %  
Peak intensity 7.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)