



Material:

* Insulation: Nylon 66 UL 94V-0

* Contact: Brass with Tin plated

Ordering Code:

CI61 ** P 1 V 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② NO. of Circuits: 02 to 06
- ③ P= Pin header
- ④ 1= 2.03 μ m(80 μ "") Min. Tin over 0.76 μ m(30 μ "") Nickel
- ⑤ V= Straight
- ⑥ Option: 00= Color Nature(Standard)

Circuits	Dimension	
	A	B
2	7.50(.295)	12.5(.492)
3	12.50(.492)	17.5(.689)
4	17.50(.689)	22.5(.886)
5	22.50(.886)	27.5(1.083)
6	27.50(1.083)	32.5(1.280)

Recommended P.C. Board Layout

Tin-Lead Process

Halogen-Free

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: 7.50-5.00mm(.295"-.197") STRAIGHT HEADERS	 瀚荃股份有限公司 CviLux Corporation			
3				DRAWN BY: Betty	09/24-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED			MATERIAL:		
2				ENGINEER: David	09/24-01'	.X \pm 0.38/.015	X' \pm 1'				
1				CHECKED BY: David	09/24-01'	.XX \pm 0.25/.010	.X' \pm	FINISH:			
SYM	NAME	DATE		REVISIONS	APPROVED BY: Alex	09/24-01'	.XXX \pm 0.15/.006	.XX' \pm	DRAWING NO. CI6101SD	PART NO. CI61**P1V00	
								SCALE	2 / 1	SHEET	1 OF 1