



Material:  
 \* Insulation: Glass filled polyester UL 94V-0  
 \* Contact: Phosphor Bronze

Ordering Code:

CB85 \*\* 2 V 1 00  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② NO. of Circuits:
- ③ Plating code:  
 2= Gold flash plated over  
 1.27μm(50μ") Nickel
- ④ Tail Style: V= Straight
- ⑤ Color: 1= Black
- ⑥ Other options: 00= Standard

A = 2.54 \* No. of Spaces  
 B = A + 3.0

△ \* Available in 4 through 40 circuits

Recommended P.C. Board Layout

Tin-Lead Process

RoHS Compliant

△4	Sun	7/30-19'	ECRB119044/ECNT119166	 <b>2019.08.08</b> <b>ISSUED</b>			DATE	UNIT: mm / inch	TITLE: 2.54MM(.100") DUAL ROW BOARD MOUNT CONNECTOR	 瀚荃股份有限公司 CviLux Corporation					
△3	Sandy	5/19-08'	ECR08044-1/ECN08213		DRAWN BY: Sun	7/30-19'	TOLERANCE UNLESS OTHERWISE SPECIFIED		MATERIAL:		DRAWING NO. CB8501SF	PART NO. CB85**2V100			
△2	Bill	9/7-07'	ECR07111-0/ECN07372		ENGINEER: Sun	7/30-19'	.X ± 0.30 / .012 X' ± 1"		FINISH:		SCALE 4 / 1	SHEET 1 OF 1			
△1	Eisley	3/3-06'	ECR06017-0/ECN06071		CHECKED BY: Eisley	8/02-19'	.XX ± 0.20 / .008 X' ±								
SYM	NAME	DATE	REVISIONS		APPROVED BY: Eisley	8/02-19'	.XXX ± 0.10 / .004 X' ±								