



Wire Range	Insulation Diameter	Reel Q'ty
AWG #22~#28	1.70 (.067) MAX.	10,000 PCS.

Ordering Code :

CI32 T02 1 B E 0
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Type: T02= AWG #22~#28
- ③ Plating:
 - 1= Tin plated over 1.27 μ m(50 μ ") Nickel
 - 2= Gold flash plated over Nickel
 - A= Selective Gold flash plated over Nickel
 - B= Selective 0.38 μ m(15 μ ") Gold plated over 1.27 μ m(50 μ ") Nickel
 - C= Selective 0.76 μ m(30 μ ") Gold plated over 1.27 μ m(50 μ ") Nickel
- ④ Material: B= Brass, P= Phosphor Bronze
- ⑤ Plating method: E= Pre-tinned
P= Post plating
- ④② ⑥ Other Option: 0=Standard

SEC.: A-A

SEC.: B-B

RoHS Compliant

SYM	NAME	DATE	REVISIONS	APPROVED BY:	DATE	UNIT: mm / inch	TITLE:	瀚荃股份有限公司 CviLux Corporation
④	Ken	8/25-16'	ECRB116054/ECNT116188			UNIT: mm / inch	CRIMP TERMINAL	
③	Sun	10/25/05"	ECN05362	DRAWN BY: Ken	8/26-16'	TOLERANCE UNLESS OTHERWISE SPECIFIED .X \pm 0.20/.008 X' \pm 1" .XX \pm 0.10/.004 X' \pm .XXX \pm 0.05/.002 .XX' \pm	MATERIAL:	
②	Eisley	6/16/05"	ECN05214	ENGINEER: Sun	8/29-16'		FINISH:	
①	SUN	11/4/03"	ECN03385	CHECKED BY: Eisley	9/01-16'		DRAWING NO. CI3203SL	PART NO. CI32T02****
		SCALE	6 / 1	SHEET 1 OF 1				

CVILUX CORP
 2016.09.08
 ISSUED