



Material:

- * Insulation: Nylon 66 UL 94V-2
Color Nature
- * Contact: Brass

Ordering Code:

CI31 ** P * Y 00
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
1= 3.05μm(120μ") Min. Tin plated over 0.76μm(30μ") Nickel
2= Gold Flash plated over 1.27μm(50μ") Nickel
3= 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel
4= 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- ⑤ Tail Style: Y= Reverse Base
- ⑥ Option: 00= Standard

(2 through 5 circuits)

(6 through 20 circuits)

A = 2.54 x No. of Spaces

B = A + 2.54

* Available in 2 through 20 circuits

Recommended P.C. Board Layout

Tin-Lead Process

Halogen-Free

RoHS Compliant

④						UNIT: mm / inch	TITLE: 2.54MM(.100")
③	Karen	8/05-08'	ECN08378	DRAWN BY: Karen	8/05-08'	TOLERANCE UNLESS OTHERWISE SPECIFIED	REVERSE RIGHT ANGLE HEADERS
②	Sandy	8/14/06'	ECN06275/ECR06020-2	ENGINEER: Eisley	8/05-08'	.X ± 0.30/.012 X: ± 1'	MATERIAL:
①	SUN	2/11/04'	ECN04063	CHECKED BY: David	8/05-08'	.XX ± 0.20/.008 X: ±	FINISH:
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	8/05-08'	.XXX ± 0.10/.004 X: ±	



瀚荃股份有限公司
CviLux Corporation

DRAWING NO.	CI3104SH	PART NO.	CI31**P*Y00
SCALE	2 / 1	SHEET	1 OF 1