



- Soldering Bath
- WSB 150 Soldering Bath 150 W - 24 V
- Accessory for WT series soldering stations and WR series rework stations
- For tin coating and preparation of electronics components and leads
- Also used to clean excess solder from component leads
- Precision temperature control / 150° F - 850° F / 50° C - 454° C
- Heated surface - 150 W: Soldering bath - 2.3" x 1.2" x 0.75" / 58 mm x 30 mm x 19 mm
- Compatible with lead free solders
- ESD safe

WSB 150 Soldering bath

Product no.: T0052704299N

Dimensions L x W x H (mm)	175 x 120 x 54
Dimensions L x W x H (inches)	6.89 x 4.72 x 2.13
Weight (approx.) in kg	---
Voltage	24 V
Power	150 W
Channels	---
Temperature range (depends on tool) °C	66 - 454
Temperature range (depends on tool) °F	150 - 850
Temperature accuracy °C	---
Temperature accuracy °F	---
Temperature accuracy for hot air °C	---
Temperature accuracy for hot air °F	---
Temperature stability °C	---
Temperature stability °F	---
Equipotential bonding socket	---
Display	---
Additional vacuum pump	---
Max. hot air flow rate l/min (depends on tool)	---
Capacity l/min	---
Max. vacuum	---
Interface	---