



This General Purpose Handle is **supplied with reinforced cable for jobs with high-power requirements** (e.g. ground plane soldering).

It features a soft foam grip which provides thermal insulation. It is also perfect for SMDs.

Its ergonomics and the short-distance tip-to-grip also ensures greater results and comfort.

T245G is supplied with the thermal insulation foam grip and 1,5m (4.9ft) cable.

It works with C245 Cartridge Range, which are easily replaceable by using JBC Cartridge Exchanger.

Easy grip replacement

You can easily change the damaged T6057 Grips for T245 Handles by using the Slide-on tab.

**Don't believe us...
TRY IT!**



REFERENCE

T245-GA

PRODUCT COMPOSITION

- 1 T245G General Purpose Handle with reinforced cable (cartridge not included)

SPECIFICATIONS

Cable length 1.5 m
ESD safe Meet ANSI/ESD S20.20-2021

WEIGHT AND DIMENSIONS

Tool 145 x 20 x 20 mm / 0.07 kg.
5.71 x 0.79 x 0.79 in / 0.15 lb.
Package 235 x 40 x 40 mm / 0.12 kg.
9.25 x 1.57 x 1.57 in / 0.25 lb.

CONNECTABLES



CDS

Precision Soldering Station



CDB

Soldering Station

Modular System



DI

1-Tool Control Unit



DDE

2-Tool Control Unit



DME

4-Tool Control Unit

Accessories



F3435

Fume extractor for T245 ø 6 mm



F3449

Fume extractor for T245 ø 4 mm



0016057

Grips for T245 Handles

Consumables



0021530

Black Grips for T245/ T245G/ T245P



0021528

Blue Grips for T245 / T245G / T245P



OB2000

Sealing plug for T245/T470