

## LEILA-Y-RS

~10° spot beam. 14.8 mm high assembly with black holder, installation tape and pins.

## SPECIFICATION:

Dimensions	Ø 21.6
Height	14.8 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




## MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
LEILA-Y-RS	Single lens	PMMA	clear	gloss	
LEILA-Y-HLD	Holder	PC	black	gloss	
LEILA-Y-TAPE	Tape	Acryl tape			

## ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA18089_LEILA-Y-RS	1800	180	180	7.6
» Box size: 476 x 273 x 197 mm				





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### OPTICAL RESULTS (MEASURED):





LED XP-G4  
 FWHM / FWTM 13.0° / 21.0°  
 Efficiency 87 %  
 Peak intensity 14.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED XP-L RGBW HD  
 FWHM / FWTM 18.0° / 28.0°  
 Efficiency 82 %  
 Peak intensity 7.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type RGBW  
 Required components:



Light distribution files



LED XP-L RGBW HI  
 FWHM / FWTM 13.0° / 24.0°  
 Efficiency 81 %  
 Peak intensity 11.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:





Light distribution files

#### OPTICAL RESULTS (MEASURED):





LED NVSW719AC  
 FWHM / FWTM 12.0° / 21.0°  
 Efficiency 87 %  
 Peak intensity 15.3 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED OSLO Pure 1414  
 FWHM / FWTM 19.0° / 29.0°  
 Efficiency 82 %  
 Peak intensity 7.3 cd/lm  
 LEDs/each optic 4  
 Light colour/type RGBW  
 Required components:



Light distribution files



LED OSLO Square CSSRM2/CSSRM3  
 FWHM / FWTM 11.0° / 20.0°  
 Efficiency 87 %  
 Peak intensity 17.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files



#### OPTICAL RESULTS (SIMULATED):





LED Bridgelux SMD 3535 (3B1)  
 FWHM / FWTM 15.0° / 26.0°  
 Efficiency 88 %  
 Peak intensity 10.9 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED J Series 3030C  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 88 %  
 Peak intensity 14.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED J Series 5050B 6V K Class  
 FWHM / FWTM 20.0° / 41.0°  
 Efficiency 79 %  
 Peak intensity 4.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED XHP35 HD  
FWHM / FWTM 18.0° / 35.0°  
Efficiency 79 %  
Peak intensity 6 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED XHP35 HI  
FWHM / FWTM 14.0° / 26.0°  
Efficiency 87 %  
Peak intensity 11.4 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED XHP35.2 HI  
FWHM / FWTM 18.0° / 32.0°  
Efficiency 83 %  
Peak intensity 7.3 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED	XM-L RGBW (XMLDCL HD)
FWHM / FWTM	22.0° / 36.0°
Efficiency	80 %
Peak intensity	4.7 cd/lm
LEDs/each optic	1
Light colour/type	RGBW
Required components:	



Light distribution files




LED	XM-L2
FWHM / FWTM	16.0° / 30.0°
Efficiency	85 %
Peak intensity	8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files



LED	XM-L3
FWHM / FWTM	15.0° / 29.0°
Efficiency	80 %
Peak intensity	8.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED XP-E  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 90 %  
Peak intensity 26.7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED XP-E2  
FWHM / FWTM 9.0° / 18.0°  
Efficiency 91 %  
Peak intensity 30 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED XP-G2  
FWHM / FWTM 11.0° / 21.0°  
Efficiency 90 %  
Peak intensity 19 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED XP-G3  
 FWHM / FWTM 13.9° / 25.4°  
 Efficiency 85 %  
 Peak intensity 11.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED XP-G4 HI  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 88 %  
 Peak intensity 19.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED XP-GR  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 92 %  
 Peak intensity 34.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED XP-L RGBW HD  
 FWHM / FWTM 18.0° / 28.0°  
 Efficiency 84 %  
 Peak intensity 7.9 cd/Im  
 LEDs/each optic 1  
 Light colour/type RGBW  
 Required components:



Light distribution files



LED XP-L RGBW HI  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 85 %  
 Peak intensity 12.8 cd/Im  
 LEDs/each optic 1  
 Light colour/type RGBW  
 Required components:



Light distribution files




LED XP-L2  
 FWHM / FWTM 18.0° / 32.0°  
 Efficiency 80 %  
 Peak intensity 6.7 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:

Light distribution files

#### OPTICAL RESULTS (SIMULATED):





LED XP-L2  
FWHM / FWTM 18.0° / 32.0°  
Efficiency 81 %  
Peak intensity 7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED XP-LR  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 91 %  
Peak intensity 26.7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files



LED XQ-E HD  
FWHM / FWTM 14.0 + 16.0° / 27.0 + 26.0°  
Efficiency 87 %  
Peak intensity 10.2 cd/lm  
LEDs/each optic 2  
Light colour/type White  
Required components:



Detector Image: Illuminance		Zemax
20.2.2024		Zemax OpticStudio 21.3
Simulation: LED, 1000 Surfaces, 1.000mm		
Size: 2000.000 x 2.000 x 0.111mm, 0.000 x 0.000 x 0.000mm		
Wavelength: 450.0nm - 650.0nm (nm)		
Total Power: 1.7128W (1.7128W)		




Light distribution files




#### OPTICAL RESULTS (SIMULATED):



LED XQ-E HI  
FWHM / FWTM 16.0 + 18.0° / 29.0 + 26.0°  
Efficiency 88 %  
Peak intensity 9.2 cd/Im  
LEDs/each optic 2  
Light colour/type White  
Required components:




Detector Image: Illuminance  
Zemax OptiStudio 21.3



Light distribution files




LED LUXEON 5050 Round LES  
FWHM / FWTM 22.0° / 40.0°  
Efficiency 81 %  
Peak intensity 4.5 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED LUXEON 5050 Square LES  
FWHM / FWTM 20.0° / 40.0°  
Efficiency 81 %  
Peak intensity 4.7 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):





LED LUXEON CZ  
FWHM / FWTM 8.0° / 16.0°  
Efficiency 91 %  
Peak intensity 35.6 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED LUXEON HL2X-V  
FWHM / FWTM 14.0° / 26.0°  
Efficiency 88 %  
Peak intensity 11.4 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED LUXEON HL2Z  
FWHM / FWTM 11.0° / 24.0°  
Efficiency 87 %  
Peak intensity 16.1 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED LUXEON HL4X  
 FWHM / FWTM 18.0° / 32.0°  
 Efficiency 85 %  
 Peak intensity 7.2 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED LUXEON HL4Z  
 FWHM / FWTM 14.0° / 24.0°  
 Efficiency 89 %  
 Peak intensity 13.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED LUXEON Rubix  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 92 %  
 Peak intensity 33.2 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED LUXEON TX  
 FWHM / FWTM 12.0° / 23.0°  
 Efficiency 88 %  
 Peak intensity 16 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED LUXEON Z ES  
 FWHM / FWTM 10.0° / 18.0°  
 Efficiency 90 %  
 Peak intensity 26 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED SFT-12R-W-A  
 FWHM / FWTM 8.0° / 14.0°  
 Efficiency 91 %  
 Peak intensity 37.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED SFT-25R-W-A  
 FWHM / FWTM 10.0° / 16.0 + 18.0°  
 Efficiency 91 %  
 Peak intensity 28.1 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED SST-20 Gen2  
 FWHM / FWTM 12.0° / 20.0°  
 Efficiency 89 %  
 Peak intensity 19.1 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED SST-20 Gen2  
 FWHM / FWTM 12.0° / 20.0°  
 Efficiency 89 %  
 Peak intensity 18.3 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED SST-20F-W  
 FWHM / FWTM 14.0° / 24.0°  
 Efficiency 88 %  
 Peak intensity 11.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED SST-25-W  
 FWHM / FWTM 14.0 + 12.0° / 22.0°  
 Efficiency 87 %  
 Peak intensity 14 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED SST-36F-W  
 FWHM / FWTM 19.0 + 18.0° / 30.0°  
 Efficiency 85 %  
 Peak intensity 7.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED NCSxE17A  
FWHM / FWTM 20.0° / 42.0°  
Efficiency 78 %  
Peak intensity 4.3 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:



Light distribution files




LED NCSxE17A  
FWHM / FWTM 24.0° / 42.0°  
Efficiency 76 %  
Peak intensity 3.6 cd/lm  
LEDs/each optic 4  
Light colour/type RGBW  
Required components:



Light distribution files



LED NCSxE17A  
FWHM / FWTM 22.0° / 41.0°  
Efficiency 79 %  
Peak intensity 4.3 cd/lm  
LEDs/each optic 4  
Light colour/type RGBW  
Required components:




Light distribution files



#### OPTICAL RESULTS (SIMULATED):




LED NF2x757G  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 88 %  
 Peak intensity 13.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED NFSx757G  
 FWHM / FWTM 8.0° / 20.0°  
 Efficiency 88 %  
 Peak intensity 24 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED NVSB219GL-L1  
 FWHM / FWTM 14.0° / 22.0° + 23.0°  
 Efficiency 88 %  
 Peak intensity 13.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type Blue  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED NVSC219GL-L1  
 FWHM / FWTM 14.0° / 24.0°  
 Efficiency 87 %  
 Peak intensity 13.6 cd/m  
 LEDs/each optic 1  
 Light colour/type Royal Blue  
 Required components:



Light distribution files




LED NVSE219GL-L1  
 FWHM / FWTM 14.0° / 24.0°  
 Efficiency 88 %  
 Peak intensity 13.4 cd/m  
 LEDs/each optic 1  
 Light colour/type Cyan  
 Required components:



Light distribution files



LED NVSG219GL-L1  
 FWHM / FWTM 14.0° / 23.0°  
 Efficiency 88 %  
 Peak intensity 13.7 cd/m  
 LEDs/each optic 1  
 Light colour/type Green  
 Required components:




Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED NVSW219C-V2  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 90 %  
Peak intensity 21.8 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED NVSW219F  
FWHM / FWTM 14.0° / 25.0°  
Efficiency 88 %  
Peak intensity 12 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED NVSW519A  
FWHM / FWTM 18.0° / 30.0°  
Efficiency 81 %  
Peak intensity 7.8 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED NVSxE21A  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 86 %  
 Peak intensity 15.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED OSCONIQ P 3030  
 FWHM / FWTM 10.0° / 18.0°  
 Efficiency 90 %  
 Peak intensity 25.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED OSCONIQ P 3737 (3W version)  
 FWHM / FWTM 16.0° / 28.0°  
 Efficiency 87 %  
 Peak intensity 9.2 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED: OSCONIQ S 5050 (Q9LR32)  
FWHM / FWTM: 22.0° / 42.0°  
Efficiency: 80 %  
Peak intensity: 4.3 cd/lm  
LEDs/each optic: 1  
Light colour/type: White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED: OSLOM Black Flat (LUW HWQP)  
FWHM / FWTM: 6.0° / 14.0°  
Efficiency: 90 %  
Peak intensity: 53.1 cd/lm  
LEDs/each optic: 1  
Light colour/type: White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED: OSLOM Pure 1414  
FWHM / FWTM: 8.0° / 16.0°  
Efficiency: 91 %  
Peak intensity: 33.7 cd/lm  
LEDs/each optic: 1  
Light colour/type: White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED OSLON Square CSSRM2/CSSRM3  
FWHM / FWTM 12.0° / 24.0°  
Efficiency 88 %  
Peak intensity 15 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED OSLON Square CSSRM2/CSSRM3  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 89 %  
Peak intensity 24.9 cd/Im  
LEDs/each optic 1  
Light colour/type Far Red  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED OSLON Square Flat  
FWHM / FWTM 10.0° / 20.0°  
Efficiency 90 %  
Peak intensity 22.6 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED OSLON SSL 150  
FWHM / FWTM 9.0° / 18.0°  
Efficiency 91 %  
Peak intensity 27 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED OSLON SSL 150  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 91 %  
Peak intensity 25.4 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED OSLON SSL 80  
FWHM / FWTM 8.0° / 16.0°  
Efficiency 89 %  
Peak intensity 29.6 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files



#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED SYNIOS S2222  
FWHM / FWTM 10.0° / 16.0°  
Efficiency 91 %  
Peak intensity 26.6 cd/m  
LEDs/each optic 1  
Light colour/type Red  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED SYNIOS S2222  
FWHM / FWTM 10.0° / 16.0°  
Efficiency 91 %  
Peak intensity 27 cd/m  
LEDs/each optic 1  
Light colour/type Yellow  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED SYNIOS S2222  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 90 %  
Peak intensity 22.9 cd/m  
LEDs/each optic 1  
Light colour/type Blue  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED SYNIOS S2222  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 90 %  
Peak intensity 22.8 cd/lm  
LEDs/each optic 1  
Light colour/type Green  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED SYNIOS S2222  
FWHM / FWTM 10.0° / 18.0°  
Efficiency 90 %  
Peak intensity 23.4 cd/lm  
LEDs/each optic 1  
Light colour/type Blue  
Required components:



Light distribution files

**SAMSUNG**

LED LH351B  
FWHM / FWTM 13.0° / 24.0°  
Efficiency 86 %  
Peak intensity 13 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED Z5M3-E1  
 FWHM / FWTM 14.0° / 24.0°  
 Efficiency 89 %  
 Peak intensity 12.8 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED Z5M4  
 FWHM / FWTM 15.0° / 28.0°  
 Efficiency 87 %  
 Peak intensity 10.1 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED Z5M4-E1  
 FWHM / FWTM 14.0° / 26.0°  
 Efficiency 87 %  
 Peak intensity 10.7 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:





Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED Z5M4-E2  
 FWHM / FWTM 16.0° / 28.0°  
 Efficiency 87 %  
 Peak intensity 9.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED MGN1108MS  
 FWHM / FWTM 10.0° / 16.0°  
 Efficiency 91 %  
 LEDs/each optic 1  
 Light colour/type IR  
 Required components:



Light distribution files



LED MJN1108MS  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 92 %  
 LEDs/each optic 1  
 Light colour/type IR  
 Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)