

# Elegant

## Enclosure



EG 1230

Order no.: 32123002

\* = Available on request.

### Characteristics

Colour of enclosure group

light grey/agate grey

Protection class

IP 40

Enclosure Material

PS (polystyrene); for details see Technical Information

Scope of delivery

Lid, base, screws

### Note


Higher protection class on request.

### Dimensions

Dimensions

125 x 67 x 30 mm

Product drawing



### Technical documentation / Downloads

#### Technical drawings

3D product data in STEP format: 32123002 EG-1230.stp (1.1 MB)

Drawing for mechanical processing: 32123002 EG-1230-G.dxf (504.6 KB)

Milling contours are shown here as a DXF file. (Sub D, USB, HDMI, cable glands, ...)

Product drawing in PDF format: 32123002 EG-1230.pdf (127.2 KB)

Product drawing in DXF format: 32123002 EG-1230.dxf (782.5 KB)

#### Product information

elegant en.pdf (580.7 KB)

## Important!

---

To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a pressure compensation element.

» Additional information

## Matching accessories

---



### Rubber feet

22009000 GF

Polyurethane, 65-75 Shore

Black



### Universal clip and tip-up clip

34090000 ASC 1

Black, similar to RAL 9005



### Wall brackets, ABS

33000200 EG-WL

33000210 EG-WL DO

Only for use with EG-DO..



### Lid fixing set from above for EG 12.. - 20..

33100000 EG-DO 30

For EG 1230, 1530, 2030, not for EG..30 F



### Quick-release fastener for EG 12.. - 20.., polyamide

33000400 EG-SV



### Press-in tool for EG-SV

33000405\* EG-WZ



### Covers for keyhole suspension

33000100 EG-AK

Agate grey



Screw cover, ABS

33000300 EG-SA

Agate grey



Mounting panel, laminated paper

33012000\* EG-M 12

For EG 12..



Universal DIN rail holder TSH 35, polyamide

22035000 TSH 35

Black, similar to RAL 9005




Metal top hat rail adapter for DIN rail DIN EN 60715 TH 35

34035050 TSH 35 AL - 50

Width 50 mm, natural colour anodised

34035100 TSH 35 AL - 100

Width 100 mm, natural colour anodised



Universal rubber feet for stability of the enclosures on all surfaces

35800300 BOP-GF

Polyurethane, 65-75 Shore

Transparent



Screws (SHR) and distance bolts (DIBLZ) for mounting bosses in plastic enclosures

59006219 SHR Z KA30x6

SD = 3.0 / ND = 2.4-2.6 / KD = 5.3