

# Element / Universal

Enclosure with snap lock



U 50

Order no.: 06050000

\* = Available on request.

## Characteristics

Colour of enclosure group

light grey/graphite grey

Protection class

IP 40

Enclosure Material

PS (polystyrene); for details see Technical Information

Scope of delivery

Lid, base

## Note


If required, the locking function can be permanently fixed by means of screws.

## Dimensions

Dimensions

50 x 50 x 30 mm

Product drawing



## Technical documentation / Downloads

### Technical drawings

3D product data in STEP format: 06050000 U-50.stp (493.4 KB)

Drawing for mechanical processing: 06050000 U-50-G.dxf (515.5 KB)

Milling contours are shown here as a DXF file. (Sub D, USB, HDMI, cable glands, ...)

Product drawing in PDF format: 06050000 U-50.pdf (46.3 KB)

Product drawing in DXF format: 06050000 U-50.dxf (383.8 KB)

### Product information

element-universal en.pdf (833.2 KB)

## Important!

---

To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a pressure compensation element.

» Additional information

## Matching accessories

---



Screws (SHR) and distance bolts (DIBLZ) for mounting bosses in plastic enclosures

59006219 SHR Z KA30x6

SD = 3.0 / ND = 2.4-2.6 / KD = 5.3