



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
4	Pin Header	Copper	Sn Plated
3	Screw	Steel	M3/Zn Plated
2	Cage	Copper Alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/30	/	300/10
IEC 标准/IEC Standard:	450/32		
额定电压/电压/Rated Voltage(V)/Current(A)	AC2500		
工频耐压/Withstanding Voltage(V/1MIN)	M3, 0.5/4.43		
拧紧扭矩/Torque Tightening(N·m/Lb·in)	1.5~4/26~10		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	6.35/N=02~24P		
引线长度/Stripping length(mm)	7~8		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	Lan CHH 2020.05.16
CHKD:	Yu JZh 2020.05.16
DRAFT:	CenK 2020.05.16
NAME:	DG635-6.35-XXP-1Y-00A(H)
DRAWING NO.:	10002021
TYPE:	CUSTOMER DRAWING
SCALE:	2:1
SHEET	1/1

NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	SCALE: 2:1	SHEET
1							1/1