


DAISY-MINI-WWW-D

~65° extra wide beam. Variant with diffused lenses.

SPECIFICATION:

Dimensions	279.5 x 21.0 mm
Height	13.3 mm
Fastening	pin, screw, snaps
ROHS compliant	yes ⓘ



MATERIALS:


Component	Type	Material	Colour	Finish
F18127_DAISY-MINI-WWW-D	Linear lens	PMMA	milky	
F17667_DAISY-MINI-SHD-MET-MATT	Shade	PC	metal	matt
F17666_DAISY-MINI-SHD-MET	Shade	PC	metal	gloss
F17465_DAISY-MINI-SHD-WHT-MATT	Shade	PC	white	matt
F17034_DAISY-MINI-SHD-MATT	Shade	PC	black	matt
F17033_DAISY-MINI-SHD-WHT	Shade	PC	white	gloss
F17028_DAISY-MINI-SHD	Shade	PC	black	gloss

ORDERING INFORMATION:

Quantities for one set:

Linear lens	1
Shade	1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
F18127_DAISY-MINI-WWW-D	Linear lens	252	252	12	6.1
» Box size: 398 x 298 x 265 mm					
F17465_DAISY-MINI-SHD-WHT-MATT	Shade	252	252	4	6.2
» Box size: 398 x 298 x 265 mm					
F17028_DAISY-MINI-SHD	Shade	252	252	4	5.9
» Box size: 398 x 298 x 265 mm					
F17666_DAISY-MINI-SHD-MET	Shade	252	252	4	5.9
» Box size: 398 x 298 x 265 mm					
F17033_DAISY-MINI-SHD-WHT	Shade	252	252	4	5.9
» Box size: 398 x 298 x 265 mm					
F17667_DAISY-MINI-SHD-MET-MATT	Shade	252	252	4	6.2
» Box size: 398 x 298 x 265 mm					
F17034_DAISY-MINI-SHD-MATT	Shade	252	252	4	6.1
» Box size: 398 x 298 x 265 mm					




See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):




LED J Series 2835
FWHM / FWTM 67.0° / 91.0°
Efficiency 86 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17667_DAISY-MINI-SHD-MET-MATT




OPTICAL RESULTS (SIMULATED):



LED XQ-E HI
FWHM / FWTM 68.0°
Efficiency 67 %
LEDs/each optic 1
Light colour White
Required components:
 F17028_DAISSY-MINI-SHD




LED LUXEON 3030 2D (Round LES)
FWHM / FWTM 63.0°
Efficiency 67 %
LEDs/each optic 1
Light colour White
Required components:
 F17028_DAISSY-MINI-SHD



LED LUXEON HL1Z
FWHM / FWTM 60.0° / 76.0°
Efficiency 67 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 F17028_DAISSY-MINI-SHD




LED NCSxE17A
FWHM / FWTM 62.0°
Efficiency 65 %
LEDs/each optic 1
Light colour White
Required components:
 F17028_DAISSY-MINI-SHD




OPTICAL RESULTS (SIMULATED):




LED NFSx757G
FWHM / FWTM 65.0°
Efficiency 69 %
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD




LED NVSxE21A
FWHM / FWTM 62.0°
Efficiency 64 %
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD



LED LH231B
FWHM / FWTM 65.0° / 86.0°
Efficiency 67 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17034_DAISY-MINI-SHD-MATT




LED LM101B
FWHM / FWTM 63.0°
Efficiency 67 %
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD



OPTICAL RESULTS (SIMULATED):


SAMSUNG

LED LM28xB Series
 FWHM / FWTM 64.0°
 Efficiency 68 %
 LEDs/each optic 1
 Light colour White
 Required components:
 F17028_DAISSY-MINI-SHD




SAMSUNG

LED LM301B EVO
 FWHM / FWTM 68.0° / 92.0°
 Efficiency 87 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 F17034_DAISSY-MINI-SHD-MATT




SAMSUNG

LED LM302Z plus
 FWHM / FWTM 65.0°
 Efficiency 68 %
 LEDs/each optic 1
 Light colour White
 Required components:
 F17028_DAISSY-MINI-SHD



SAMSUNG


LED LM561B
 FWHM / FWTM 69.0 + 65.0°
 Efficiency 80 %
 LEDs/each optic 1
 Light colour White
 Required components:
 F17033_DAISSY-MINI-SHD-WHT



OPTICAL RESULTS (SIMULATED):


SAMSUNG

LED LM561B
FWHM / FWTM 68.0 + 64.0°
Efficiency 68 %
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISSY-MINI-SHD




SAMSUNG

LED LM561B
FWHM / FWTM 69.0 + 65.0°
Efficiency 80 %
LEDs/each optic 1
Light colour White
Required components:
F17465_DAISSY-MINI-SHD-WHT-MATT




SAMSUNG

LED LM561B
FWHM / FWTM 69.0 + 65.0°
Efficiency 81 %
LEDs/each optic 1
Light colour White
Required components:
F17666_DAISSY-MINI-SHD-MET



SAMSUNG

LED LM561B
FWHM / FWTM 72.0 + 70.0°
Efficiency 80 %
LEDs/each optic 1
Light colour White
Required components:
F17667_DAISSY-MINI-SHD-MET-MATT



OPTICAL RESULTS (SIMULATED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED: SEOUL 3030 FWHM / FWTM: 66.0° Efficiency: 68 % LEDs/each optic: 1 Light colour: White Required components: F17028_DAISY-MINI-SHD</p>	
<p> SEOUL SEMICONDUCTOR</p> <p>LED: SEOUL 3030 FWHM / FWTM: 68.0° / 88.0° Efficiency: 69 % Peak intensity: 0.6 cd/lm LEDs/each optic: 1 Light colour: White Required components: F17028_DAISY-MINI-SHD</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)