



PIN位图

未注尺寸请参考3D文件



尺寸公差(mm)				
0	>30	>60	>100	>150
~30	~60	~100	~150	
±0.20	±0.30	±0.50	±0.70	±1.00



技术要求/Technical requirements:	
额定电压/Rated Voltage/Current	60V AC/3A
绝缘电阻/Insulate Resistance	>100MΩ
耐压/Withstanding Voltage	850V AC 1min
防护等级/Ingress Protection	IP67
使用温度范围/Operating temperature(°C)	-25~+105
符合RoHS环保要求/Conform to RoHS	YES

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized. All rights reserved for patent, utility model or design registrations. 非经书面授权, 严禁禁止转让、复制、利用、交加本文件的内容。一经发现侵权, 侵权者将承担法律责任。 实用新型和外观设计专利的所有权利。

图纸版本	ECN	变更描述	设计人	设计日期
REV	ECN	DESCRIPTION	DRFT	DATE

		MATERIAL: 材质	SURFACE: 表面处理	
		MAT. NO./REV: 物料编码 / 版本	MAT STATUS: 物料状态	
APPD: 核准人	核准日期	NAME		
CHKD: 审核人	审核日期	SD-M8A-04P-MM-SH7001-00A (H)		
DRFT: 设计人	设计日期	DRAWING NO.	TYPE	DRAWING STATUS
		图号	图纸类型	图纸状态
		SCALE	SHEET	
		10:1	1/1	