



A = 2.54 x No. of Spaces
 B = A + 2.36
 * Available in 2 through 40 circuits



Recommended P.C. Board Layout

Notes:

* Material:

Contact: Brass

△* Pin overall Length 30.0mm Max.

Ordering Code

CH31 ** * V * **
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Plating code:
 1= 3.05μm(120μ") Min. Tin
 over 0.76μm(30μ") Nickel
 2= Gold flash plated over
 1.27μm(50μ") Nickel
- ④ V= Straight
- △⑤ Insulator: 2= PBT UL 94V-0, Color Black
 A= Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option Code:
 See Table PDF. File No. CH3101T

RoHS Compliant

⑤	Sun	10/6-08'	ECN08478/ECR08118-1		DATE	UNIT: mm / inch	TITLE: 2.54MM(.100") STRAIGHT BOARD MOUNT PIN HEADER	瀚荃股份有限公司 CviLux Corporation
④	Bill	4/14/07'	ECN07148/ECR07059-0	DRAWN BY: Sun	10/07-08'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
③	Lynn	12/13-04	ECN04465/ECR04109-0	ENGINEER: Eisley	10/07-08'	.X ± 0.30/.012 X.* ± 1*	FINISH:	DRAWING NO. CH3101SL PART NO. CH31***V***
②	Sun	4/09/04'	ECN04144	CHECKED BY: Alex	10/07-08'	.XX ± 0.20/.008 .X.* ±		SCALE 3 / 1 SHEET 1 OF 1
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/07-08'	.XXX ± 0.10/.004 .XX.* ±		