



公差等级/General	Tolerances(mm)										0.1/1/10			
0	>.3	>.6	>.10	>.18	>.30	>.50	>.80	>.120	>.180	>.250	>.315	>.400	±Z	
~	~	~	~	~	~	~	~	~	~	~	~	~		
3	6	10	18	30	50	80	120	180	250	315	400	500	±Z	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
1	Cover	PA66	UL94V-0
2	Side Housing1	PA66	UL94V-0
3	Housing	PA66	UL94V-0
4	Side Housing2	PA66	UL94V-0
5	Clamp	Copper alloy	Sn Plated
6	Spring	Stainless steel	

UL 标准 /UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/710	/	300/710
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	130/710	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	/	/
螺栓扭矩/Torque Tightening(N.m/Lb.in)	/	/	/
线径范围(硬线/软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~1.5/28~14		
间距/Pitch(mm)/线数范围/Poles	3.81/02~24P		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS标准/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL		PANTONE	7534U

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
BEDGK-3.81-XXP-11-01A(H)

DRAWING NO.: BEDGK-3.81-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	SCALE: 2:1	SHEET 1/1