

# SOLDERLESS TERMINALS


Designers  
Choice



Solderless terminals are made of pure electrolytic (ETP) copper annealed and tin plated. Insulation is color coded vinyl.

## SNAP-SPACE BUTTED SEAM


NON-INSULATED



Hand Crimp Tool  
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL	
								LENGTH	I.D.
8254	22/18	6	.25	.25	.68	.50	.030	.25	.070
8255		8	.30	.25	.68	.50	.030	.25	.070
8256		10	.32	.25	.68	.50	.030	.25	.070
8257	16/14	6	.25	.25	.68	.50	.030	.25	.090
8258		8	.30	.25	.68	.50	.030	.25	.090
8259		10	.32	.25	.68	.50	.030	.25	.135
8260	12/10	6	.28	.28	.73	.53	.040	.25	.135
8261		8	.32	.28	.73	.53	.040	.25	.135
8262		10	.32	.28	.73	.53	.040	.25	.135

VINYL-INSULATED




Hand Crimp Tool  
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL		MAX INSUL. DIA.
								LENGTH	I.D.	
8263	22/18 (Red)	6	.25	.25	.88	.70	.030	.25	.070	.145
8264		8	.30	.25	.88	.70	.030	.25	.070	.145
8265		10	.32	.25	.88	.70	.030	.25	.070	.145
8266	16/14 (Blue)	6	.25	.25	.88	.70	.030	.25	.090	.170
8267		8	.30	.25	.88	.70	.030	.25	.090	.170
8268		10	.32	.25	.88	.70	.030	.25	.090	.170
8269	12/10 (Yellow)	6	.28	.28	1.03	.83	.040	.25	.135	.250
8270		8	.32	.28	1.03	.83	.040	.25	.135	.250
8271		10	.32	.28	1.03	.83	.040	.25	.135	.250

## QUICK SLIDE BUTTED SEAM


FEMALE NON-INSULATED



Hand Crimp Tool  
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	MATES WITH MALE TAB WIDTH x THK	L	BARREL		MAX INSUL. DIA.
				LENGTH	I.D.	
8272	22/18	.187 x .020	.58	.25	.085	.145
8273		.250 x .032	.66	.25	.080	.145
8274		.187 x .020	.58	.25	.085	.145
8275	16/14	.250 x .032	.66	.25	.080	.145


FEMALE VINYL INSULATED



Hand Crimp Tool  
CAT. NO. 1345


CAT. NO.	WIRE RANGE (AWG)	MATES WITH MALE TAB WIDTH x THK	L	BARREL		MAX INSUL. DIA.
				LENGTH	I.D.	
8276	22/18 (Red)	.187 x .020	.78	.25	.085	.145
8277		.250 x .032	.87	.25	.080	.145
8278		.187 x .020	.78	.25	.085	.145
8279	16/14 (Blue)	.250 x .032	.87	.25	.080	.145
8280	12/10 (Yellow)	.250 x .032	.96	.25	.165	.250

MALE NON-INSULATED



CAT. NO.	WIRE RANGE (AWG)	MALE TAB WIDTH x THK	L	W	D	BARREL		MAX INSUL. DIA.
						LENGTH	I.D.	
8281	22/18	.187 x .020	.64	.24	.23	.25	.080	.145
8282		.250 x .032	.73	.25	.23	.25	.065	.145
8283	16/14	.187 x .020	.64	.24	.23	.25	.080	.145
8284		.250 x .032	.73	.25	.23	.25	.085	.170
8285	12/10	.250 x .032	.75	.25	.32	.25	.150	.250


MALE VINYL INSULATED



Hand Crimp Tool  
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	MALE TAB WIDTH x THK	L	W	D	BARREL		MAX INSUL. DIA.
						LENGTH	I.D.	
8286	22/18 (Red)	.187 x .020	.85	.24	.30	.24	.080	.145
8287		.250 x .032	.93	.25	.30	.24	.065	.145
8288	16/14 (Blue)	.187 x .020	.85	.24	.30	.24	.080	.145
8289		.250 x .032	.93	.25	.30	.24	.085	.170
8290	12/10 (Yellow)	.250 x .032	1.05	.25	.39	.25	.150	.250


FEMALE FULLY INSULATED NYLON



Hand Crimp Tool  
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	MATES WITH MALE TAB WIDTH x THK	L	W	D	BARREL		MAX INSUL. DIA.
						LENGTH	I.D.	
8291	22/18 (Red)	.187 x .020	.81	.30	.23	.25	.085	.145
8292		.250 x .032	.87	.37	.23	.25	.080	.145
8293	16/14 (Blue)	.187 x .020	.81	.30	.23	.25	.085	.145
8294		.250 x .032	.87	.37	.23	.25	.080	.170
8295	12/10 (Yellow)	.250 x .032	.99	.39	.32	.25	.165	.250

MALE FULLY INSULATED NYLON



Hand Crimp Tool  
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	MALE TAB WIDTH x THK	L	W	D	BARREL		MAX INSUL. DIA.
						LENGTH	I.D.	
8296	22/18 (Red)	.187 x .020	.87	.37	.30	.24	.080	.145
8297		.250 x .032	.95	.44	.30	.25	.065	.145
8298	16/14 (Blue)	.187 x .020	.87	.37	.30	.24	.080	.170
8299		.250 x .032	.95	.44	.30	.25	.085	.170
8300	12/10 (Yellow)	.250 x .032	1.05	.47	.39	.25	.150	.250