



公差等级/General	tolerance/(mm)	0.1/1.0
0	>.3	>.150
~	~.6	~.315
3	~ 10	~ 500
6	~ 18	~ 400
10	~ 30	~ 250
±0.12	±0.18	±0.22
±0.22	±0.26	±0.31
±0.31	±0.37	±0.57
±0.57	±0.80	±0.93
±1.05	±1.15	±1.60
±2.20	±2.20	±2.50
±Z		

ITEM	NAME OF PART	MATERIAL	NOTES
1	Cover	PA66	UL94V-0
2	Side Housing1	PA66	UL94V-0
3	Housing	PA66	UL94V-0
4	Side Housing2	PA66	UL94V-0
5	Clamp	Copper alloy	Sn Plated
6	Spring	Stainless steel	

UL 标准 /UL Standard:	B	C	D
额定电压/电涌 /Rated Voltage(V)/Current(A)	300/710	/	300/710
IEC 标准 /IEC Standard:			
过压类别 /Overvoltage Category /污秽等级 /Pollution Degree	III/3	III/2	II/2
额定电压/电涌 /Rated Voltage(V)/Current(A)	130/710	/	/
额定脉冲电压 (KV) /Rate Impulse Voltage(KV)	2.5	/	/
额定扭矩 /Torque Tightening(N.m/Lb.in)	/	/	/
线径范围 (裸线/带机械) /Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~1.5/28~14		
间距 /Pitch(mm) /线距范围 /Poles	3.5/02~24P		
剥线长度 /Stripping length(mm)	6~7		
使用温度范围 /Operating Temperature(°C)	-40~+105		
符合 RoHS 标准 /Conform to RoHS	Yes		
标准颜色编号 /Standard color number:			
PANTONE / RAL			PANTONE 7534U

MATERIAL: / SURFACE: /

MAT NO.: /  
 STATUS: /  
 APPD: /  
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**  
**8EDGK-3.5-XXP-11-01A(H)**

DRAWING NO.: 8EDGK-3.5-C01  
 TYPE: CUSTOMER DRAWING  
 SCALE: 2:1  
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	SCALE: 2:1	REV	TO
1								
2								
3								
4								
5								
6								

