



PCB LAYOUT



REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

NOTES1:

- UL Standard
- 1. Rated Voltage/Current : 300V / 8A
- 2. Withstanding Voltage : AC1600V/1Min.
- VDE Standard

Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(kV)	2.5KV
Rate Voltage(V)	250V
Rate Current(A)	7A

NOTES2:

- 1. Dimension shall be interpreted per ASME Y14.5-2009
- 2. Pitch : 3.50mm, Poles : N=2~12P
- 3. Operating temperature: -40°C~+105°C
- 4. Undimensioned Tolerances:

Pitch Range In mm		Nominal Dimension Range In mm						±
To	Over	To	Over	To	Over	To	Over	0.1/1n
6	10	6	35	10	15	100	150	≤
±0.15	±0.20	±0.30	±0.30	±0.60	±0.70	±1.00	±1.30	±2

- 5. RoHS Compliance



2	PIN	COPPER ALLOY Sn Plated	
1	HOLDING	PA66 UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES

DETACHED LISTS	PART NO.:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
	APPD: Aaron 10/14	NAME:	15EDGRC-3.5-XXP-1Y-12A(H)	
	CHKD: Xmm 10/14/14	TITLE:	CUSTOMER DRAWING	REV: 1.0
	DRFT: Yz 10/12/15	DRAWING NO.:	15EDGRC-3.5-C05	SHEET: 1/1
THIRD ANGLE PROJECTION		DO NOT SCALE DRAWING	SCALE:	1:1